

### TPD-1000 Series Digital Radio With Display



**TPD-1124 VHF (136-174 MHz)**  
**TPD-1424 UHF (400-470 MHz)**

5/1 Watt (VHF) – 4/1 Watt (UHF) Power Output  
VHF (136-174 MHz) – UHF (400-470 MHz)  
1024 Channel Capacity  
12.5/20/25 kHz Channel Spacing  
Dual Modes (DMR Tier II TDMA/Analog)  
Versatile Voice Calls  
Remote Kill, Stun and Revive  
Bluetooth (optional)  
Vibrate  
GPS (optional)  
Various Analog Signaling Types  
CTCSS/DCS  
ANI, 2-Tone Encode/Decode/5-Tone Selcall  
MDC-1200, Stun/Kill OTA  
Compliant with MIL-STD 810F and IP-67 Standards

### TPD-1000 Series Digital Radio Non Display



**TPD-1116 VHF (136-174 MHz)**  
**TPD-1416 UHF (400-470 MHz)**

5/1 Watt (VHF) – 4/1 Watt (UHF) Power Output  
VHF (136-174 MHz) – UHF (400-470 MHz)  
16 Channel Capacity  
12.5/20/25 kHz Channel Spacing  
Dual Modes (Analog+Digital)  
Versatile Voice Calls  
Remote Kill, Stun and Revive  
Bluetooth (optional)  
Vibrate  
Various Analog Signaling Types  
CTCSS/DCS  
ANI, 2-Tone Encode/Decode/5-Tone Selcall  
MDC-1200, Stun/Kill OTA  
Compliant with MIL-STD 810F and IP-67 Standards  
3 Year Warranty

### TP-8000R Series Recording Radio



**TP-8102R VHF (136-174 MHz)**  
**TP-8402R UHF (400-470 MHz)**

5/2 Watt (VHF) – 4/2 Watt (UHF) Power Output  
VHF (136-174 MHz) – UHF (400-470 MHz)  
512 Channels – Dynamic Grouping  
12.5/25 kHz Channel Spacing  
2-Tone Decode, Stun/Kill OTA  
2/5 Tone Selcall and DTMF ANI  
Alpha-Numeric Display  
CTCSS/DCS Enc/Dec  
Voice Scrambler – Inversion  
TOT/BCL/BCL0  
Meets Military Standards 810F  
3 Year Warranty

### TJ-3000 Series Jobsite Radio



**TJ-3100V VHF (150-174 MHz)**  
**TJ-3400U UHF (450-470 MHz)**

2 Watt Power Output  
VHF (150-174 MHz) – UHF (450-470 MHz)  
27 Channels (VHF) – 89 Channels (UHF)  
Pre-Programmed Exclusive Job-Site Frequencies  
7 Weather Channels VHF/UHF  
1 Watt Audio Output  
Alpha-Numeric Display  
CTCSS/DCS – User Programmable  
Meets Mil Std 810F and IP-54 Approved

### TS-3000 Series Handheld Radio



**TS-3116 VHF (136-174 MHz)**  
**TS-3416 UHF (400-470 MHz)**

5/1 Watt (VHF) – 4/1 Watt (UHF) Power Output  
VHF (136-174 MHz) – UHF (400-470 MHz)  
16 Channels  
Optional Voice Annunciation  
CTCSS/DCS  
700 mw Audio Output  
Time-Out-Timer (TOT)  
Power Save Mode  
VOX  
Meets Mil Std 810F and IP-54 Approved  
1 Year Warranty

### TS-2000 Series Handheld Radio



**TS-2116 VHF (136-174 MHz)**  
**TS-2416 UHF (400-470 MHz)**

2 Watt Power Output  
VHF (136-174 MHz) – UHF (400-470 MHz)  
16 Channels  
Optional Voice Annunciation  
CTCSS/DCS  
700 mw Audio Output  
Time-Out-Timer (TOT)  
Power Save Mode  
VOX  
Meets Mil Std 810F and IP-54 Approved  
1 Year Warranty

**Accessories available include: chargers, programming cables and software, speaker mics and more.  
Call for availability and pricing.**

# Call For Quantity Discount!



## TM-2000 Series

**TM-2102 25W (VHF) (136-174 MHz)**  
**TM-2402 25W (UHF) (400-470 MHz)**

- 512 Channel Capability – Up to 32 Groups (Dynamic)
- Four Programmable Function Buttons
- User Selectable Squelch Level
- 12.5/25 kHz Channel Bandwidth
- Compandered Audio
- DTMF Encode/Decode, DTMF ANI
- Alpha-Numeric Dot Matrix Display
- DE-15 Data Connector
- Remote Stun/Revive
- Voice Scrambler – Inversion
- Busy Channel Lockout
- Repeater Ready (XRC-31)



## TM-8000 Series

**TM-8102 (VHF) (136-174MHz)**  
**TM-8402A (UHF) (400-470 MHz)**  
**TM-8402B (UHF) (450-520 MHz)**

- 512 Channel Capability – Up to 32 Groups (Dynamic)
- Four Programmable Function Buttons
- User Selectable Squelch Level
- 12.5/25 kHz Channel Bandwidth
- Compandered Audio
- DTMF Encode/Decode, DTMF ANI
- Alpha-Numeric Dot Matrix Display
- DE-15 Data Connector
- Remote Stun/Revive
- Voice Scrambler – Inversion
- Busy Channel Lockout
- Repeater Ready (XRC-31)

### UDM-240ZH



Main body



Charger



Adaptor

## UDM-240 Short Range Digital Communication

**UDM-240ZH Speaker Microphone/Intercom**  
**UDM-240ZV Vehicle Repeater**

Communicate up to 320' between ZH & ZV, communicate up to 160' between ZH units. Perfect for: communication between staff in store or restaurant; dual control head radio as on fire engines; shorter range applications such as Police and Ambulance; remote operation vehicles like tow trucks, cherry pickers, delivery vehicles.

- 2.4 GHz ISM Band – Zigbee Wireless
- License Free
- 16 Channels x 99 Groups, 64,000 ID's Per Channel for security
- Intercom Capability up to 16 ZH units
- Communicate up to 160'
- Out Of Range and Entry Alert
- Desktop Charger (Vehicle Mount)
- Displays Channel & Volume Status
- Earphone Jack 3.5 mm (Receive Only)
- Group/Individual ID Mode Selectable
- Operating Time up to 8 Hours
- IP-67 rating

\*INT Mode: Able to call the inner line and communicate between UDM-240ZH and UDM240ZH.

\*PTT Mode: Enables remote control of 2-way radio or mobile radio through UDM-240ZH and UDM-240ZV (for Motorola, Vertex, Kenwood, Icom mobile)

### UDM-240ZV



Mobile dongle



External ANT(Magnet)



Cable