

70/25V Equipment



SPG66TC *With Volume Control*

6" 70/25V Ceiling Speaker w/Transformer

- 5W dual 70/25V transformer (with taps of 5W, 2.5W, 1W, 0.5W, 0.25W & 8 Ohms)
- 10W RMS / 15W Max Power
- Cutout Dimensions: 9.5" Dia



G86TG

G86TCG *With Volume Control*

8" Dual Cone Ceiling Speaker w/Transformer

- 5W dual 70/25V transformer (with taps of 5W, 2.5W, 1W, 0.5W, 0.25W & 8 Ohms)
- Cutout Dimensions: 11.3" Dia



TS8

Tile Bracket For 8" Ceiling Speaker

- Steel, Rust Resistant construction
- Designed for G86 speakers and STH8 back can
- Maximum span of 24"



STH8

Back Can For 8" Ceiling Speaker

- Heavy gauge steel construction
- 4 combination knockouts 1/2" to 3/4"
- 4 J clips for mounting of baffles



SPC15T

8" 70/25V Weatherproof PA Speaker

- 70/25V Line Transformer
- 25V line wattage taps for 15, 10 and 3.7 watts
- 70V line wattage taps for 15, 10, 5, 3 and 1 watts



SPC40RT

6.5" x 11" 70/25V Weatherproof PA Speaker

- 70/25V Line Transformer
- Line wattage taps for 32, 16, 8, 5 and 2 watts
- 32W Max power, 8 ohm impedance



MCHH100A

Dynamic Handheld Mic

- Great for speech, vocals and karaoke.
- Stand adapter, 15' XLR cable and carry case included



MHL5S

Adjustable 6" Gooseneck Tabletop Mic

- 3-Way Toggle Switch
- High and Low Impedance Switch on Base
- XLR Connector with 5' Coil Cord



PBM-30

30W 2ch Mixer/Amplifier

- Microphone and source mixing ability
- Telephone paging interface
- Auto mute function & manual mute contacts
- Bass & Treble tone controls
- Music on hold output with separate level control
- Two MIC inputs & Auto summing stereo AUX input
- 600 Ohm telephone line input with level control
- Accessory AC outlet
- 4/8/16 Ohms & 70/25V outputs



PAT20TB

20W Mobile Amplifier w/2-Way Communication

- Suitable for motor vehicle or nautical applications
- Plug in cigarette lighter adapter
- Controls for: Auxiliary, Master Volume and Tone
- Auxiliary sound input jack on rear panel
- Built in speaker and push to talk microphone
- RMS Power: 20W • Impedance: 4 or 8 Ohms

REPLACEMENT MIC = DM520P



WB86T

8" Dual Cone Wall Speaker w/Transformer

- 5W dual 70/25V transformer (with taps of 5W, 2.5W, 1W, 0.5W, 0.25W & 8 Ohms)
- 10W RMS / 15W Max Power
- Fully enclosed solid wood construction
- *This speaker does not have a volume control

4 / 8 Ohm Equipment



SPC5P



SPC10, SPC10/4



SPC15



SPC15R



SPC30



SPC40



ASPC20



AES4 / CBS-4

SPC5P

5" White Weatherproof PA Speaker – 8 ohm, 12 watt

SPC10

6" Weatherproof Aluminum PA Horn – 8 ohm, 15 watt

SPC10/4

6" 4 Ohm Weatherproof Aluminum PA Horn – 4 ohm,

SPC15

8" Weatherproof Aluminum PA Horn – 8 ohm, 25 watt

SPC15R

5" x 8" Weatherproof Aluminum PA Horn – 8 ohm, 25 watt

SPC30

15" Weatherproof Aluminum PA Horn – 8 ohm, 65 watt

SPC40

6.5" x 11" Weatherproof PA Horn – 8 ohm, 40 watt

ASPC20

6" Amplified Weatherproof ABS Plastic PA Speaker

AES4

5"x5" Amplified Extension Speaker – 4/8 ohm

CBS-4

4" 10W Extension Speaker – 4/8 ohm