

POWER ZONE AMPLIFIERS

Features Include: SEPP A/B Class Amplifier Designs, Illuminated Crunch Logo, Top Mount Controls, Bass Boost w/Variable Bass Equalization, Rugged PWM Power Supply, Built In System Diagnostics, Daisy Chain Line Outputs, Versa Cross Electronic Crossover, Stereo/Mono Amplifier Mode Switch, Speaker Lead High Level Inputs.



1ch Class A/B

PZT1500.1

1 x 375w @ 4Ω / 1 x 750w @ 2Ω / 1 x 1500w @ 1Ω

2ch Class A/B

PZT1400.2

2 x 350w @ 4Ω / 2 x 700w @ 2Ω / 1 x 1400w @ 4Ω

PZT1100.2

2 x 275w @ 4Ω / 2 x 550w @ 2Ω / 1 x 1100w @ 4Ω

PZT500.2

2 x 125w @ 4Ω / 2 x 250w @ 2Ω / 1 x 500w @ 4Ω

4ch Class A/B

PZT1400.4

4 x 175w @ 4Ω / 4 x 350w @ 2Ω / 2 x 700w @ 4Ω

PZT900.4

4 x 115w @ 4Ω / 4 x 225w @ 2Ω / 2 x 450w @ 4Ω

GROUND POUNDER AMPLIFIERS

Features Include: Twin Coil Isolation Design, Twin Turbo MOSFET Exponential Variable Power Supply, 24dB Adjustable Crossovers, Bass Thrust With Variable Bass Equalization, Blue Illuminated Crunch Logo (Fixed Illumination or Scrolling Illuminating V), RCA Line Outputs, 4-0 Gauge Power Connectors, Remote Bass Control Included With Mono Block Amps.



1ch Class A/B

GPV2000.1

1 x 500w @ 4Ω / 1 x 1000w @ 2Ω / 1 x 2000w @ 1Ω

2ch Class A/B

GPV1000.2

2 x 250w @ 4Ω / 2 x 500w @ 2Ω / 1 x 1000w @ 4Ω

GPV700.2

2 x 175w @ 4Ω / 2 x 350w @ 2Ω / 1 x 700w @ 4Ω

4ch Class A/B

GPV1600.4

4 x 200w @ 4Ω / 4 x 400w @ 2Ω / 2 x 800w @ 4Ω

GPV1000.4

4 x 125w @ 4Ω / 4 x 250w @ 2Ω / 2 x 500w @ 4Ω

POWER ONE AMPLIFIERS

Features: Not Yet Available At Press Time. Call For Updated Information.



1ch Class A/B

P1 2000.1

1 x 500w @ 4Ω / 1 x 1000w @ 2Ω / 1 x 2000w @ 1Ω

2ch Class A/B

P1 1000.2

2 x 250w @ 4Ω / 2 x 500w @ 2Ω / 1 x 1000w @ 4Ω

P1 600.2

2 x 150w @ 4Ω / 2 x 300w @ 2Ω / 1 x 600w @ 4Ω

4ch Class A/B

P1 1000.4

4 x 125w @ 4Ω / 4 x 250w @ 2Ω / 2 x 500w @ 4Ω

P1 600.4

4 x 75w @ 4Ω / 4 x 150w @ 2Ω / 2 x 300w @ 4Ω

5ch Class A/B

P1 5000.5

4 x 125w + 1 x 300 @ 4Ω / 4 x 250w + 1 x 500 @ 2Ω

GROUND POUNDER SPEAKERS

Features Include: Silver Alpha-Cellulose Cones, Neodymium Mylar Soft Dome Tweeters, Moisture Resistant Rubber Surrounds, Anti Resonant Speaker Frames, External 12dB Passive Inline Crossover.



GRP6.5C

6-1/2" Component Set - 60w RMS/300w MAXX



GRP62CX

6-1/2" Coaxial - 60w RMS/300w MAXX

GRP693

6 x 9" 3-Way - 80w RMS/400w MAXX

GROUND POUNDER SUBWOOFERS

Features Include: Polypropylene Cone, Rubber Surround, Stamped Steel Basket, Nickel Plated Push Terminals, Heat Dispersing Ported Nickel Plated Back Plate, Protective Rubber Magnet Wrap.



GPV12D2

12" Dual 2Ω Voice Coil Sub - 600w RMS/1200w MAXX

GPV12D4

12" Dual 4Ω Voice Coil Sub - 600w RMS/1200w MAXX

GPV15D2

15" Dual 2Ω Voice Coil Sub - 700w RMS/1400w MAXX

