

**POWERONE AMPLIFIERS**

**CRUNCH**  
FEEL THE POWER



- SEPP A/B Analog Class
- 4/2 Ohm Stable Multi Channel Models
- 4/2/1 Ohm Stable Mono Models
- PWM Power Supply
- Fully Adjustable 12dB Crossovers
- Input Sensitivity From .2 to 5 Volts
- High & Low Level Inputs For Full Range Models
- Bass Remote Included with P12000.1
- Subsonic Filter & Bass EQ

<b>P1 2000.1</b>	1 x 500w @ 4Ω	1 x 1000w @ 2Ω	1 x 1000w @ 1Ω
<b>P1 600.2</b>	2 x 150w @ 4Ω	2 x 300w @ 2Ω	1 x 600w @ 4Ω
<b>P1 1000.2</b>	2 x 250w @ 4Ω	2 x 500w @ 2Ω	1 x 1000w @ 4Ω
<b>P1 600.4</b>	4 x 75w @ 4Ω	4 x 150w @ 2Ω	2 x 300w @ 4Ω
<b>P1 1000.4</b>	4 x 125w @ 4Ω	4 x 250w @ 2Ω	2 x 500w @ 4Ω
<b>P1 5000.5</b>	4 x 125w + 1 X 300w @ 4Ω	4 x 200w + 1 x 500 @ 2Ω	

**POWERONE SUBWOOFERS**

**CRUNCH**  
FEEL THE POWER



- Dual 4 Ohm Voice Coils
- High Energy Magnet with ABS Motor Cap
- Paper Cone
- Ultra Rigid Stamped Steel Basket
- Multi Layer High Temp Voice Coil
- Front Plate & Voice Coil Cooling
- Stitched & Glued Foam Surround

<b>P1 12D4</b>	12" Dual 4Ω Voice Coil • 700w Maximum / 300w RMS
----------------	--

**POWERONE SPEAKERS**

**CR**  
FEEL



- Neo Mylar Soft Dome Tweeter
- Silver Alpha Cellulose Cones
- Moisture Resistant Rubber Surround
- Anti Resonant Stamped Steel Basket
- Installation Hardware Included

<b>P1 653</b>	6-1/2" Coaxial • 800w Maximum / 55w Continual
<b>P1 693</b>	6 x 9" Three Way • 1000w Maximum / 70w Continual
<b>P1 6.5C</b>	6-1/2" Component Set • 800w Maximum / 60w Continual

**GROUND POUNDER AMPLIFIERS**

**CRUNCH**  
FEEL THE POWER



- SEPP A/B Analog Class
- 4/2 Ohm Stable Multi Channel Models
- 4/2/1 Ohm Stable Mono Models
- PWM Power Supply
- Fully Adjustable 12dB Crossovers
- Input Sensitivity From .2 to 5 Volts
- High & Low Level Inputs For Full Range Models
- Bass Remote Included with GPV2100.1
- Subsonic Filter & Bass EQ

<b>GPV 2100.1</b>	1 x 525w @ 4Ω	1 x 1050w @ 2Ω	1 x 2100w @ 1Ω
<b>GPV 1100.2</b>	2 x 275w @ 4Ω	2 x 550w @ 2Ω	1 x 1100w @ 4Ω
<b>GPV 1200.4</b>	4 x 150w @ 4Ω	4 x 300w @ 2Ω	2 x 600w @ 4Ω

**GROUND POUNDER SUBWOOFERS**

**CRUNCH**  
FEEL THE POWER



- Polypropylene Cone
- Rubber Surround
- Stamped Steel Frame
- Heat Dispersing Ported Back Plate
- Dual Spider Technology
- Nickel Plated Terminals
- Rubber Magnet Boot

<b>GPV12D2</b>	12" Dual 2Ω Voice Coil • 1200w Maximum / 600w RMS
<b>GPV12D4</b>	12" Dual 4Ω Voice Coil • 1200w Maximum / 600w RMS

**MEAN MACHINE AMPLIFIERS**

**AUTOTEK**



- A/B Analog Class
- 4/2 Ohm Stable Multi Channel Models
- 4/2/1 Ohm Stable Mono Models
- High Speed MOSFET Output Devices
- Variable Low Pass, High Pass, Band Pass
- Built In System Diagnostics

<b>M1500.1</b>	1 x 325w @ 4Ω	1 x 750w @ 2Ω	1 x 1500w @ 1Ω
<b>M2500.1</b>	1 x 625w @ 4Ω	1 x 1250w @ 2Ω	1 x 2500w @ 1Ω
<b>M4000.1</b>	1 x 1000w @ 4Ω	1 x 2000w @ 2Ω	1 x 4000w @ 1Ω
<b>M1600.2</b>	2 x 400w @ 4Ω	2 x 800w @ 2Ω	1 x 1600w @ 4Ω
<b>M3200.2</b>	2 x 800w @ 4Ω	2 x 1600w @ 2Ω	1 x 3200w @ 4Ω
<b>M1000.4</b>	4 x 125w @ 4Ω	4 x 250w @ 2Ω	2 x 500w @ 4Ω
<b>M2000.4</b>	4 x 250w @ 4Ω	4 x 500w @ 2Ω	2 x 1000w @ 4Ω

**AUTOTEK SUBWOOFERS**

**AUTOTEK**



- Non-Pressed Pulp Paper Cone
- Stitched & Glued Foam Surround
- Stamped Steel Frame
- Multi Layer High Temp Voice Coil
- Front Plate & Voice Coil Cooling
- Rubber Magnet Boot

<b>M12D4</b>	12" Dual 4Ω Voice Coil • 1000w Maximum / 500w RMS
<b>ATX12D4</b>	12" Dual 4Ω Voice Coil • 700w Maximum / 350w RMS