

D6 SERIES


D610D2	10" Dual 2Ω Voice Coil • 500 Watts RMS
D610D4	10" Dual 4Ω Voice Coil • 500 Watts RMS
D612D2	12" Dual 2Ω Voice Coil • 600 Watts RMS
D612D4	12" Dual 4Ω Voice Coil • 600 Watts RMS
D615D2	15" Dual 2Ω Voice Coil • 750 Watts RMS
D615D4	15" Dual 4Ω Voice Coil • 750 Watts RMS

- Hard Anodized Alloy Cone & Dust Cap
- EPDM "Omega" Surrounds
- Cast Aluminum Basket
- Dual Mirror Image Flat Spiders
- Isolated Heavy Duty Lead Wire
- Intercooled Motor Design with Vented Pole Piece
- Ferrite Magnet
- Available in Dual 2Ω or Dual 4Ω 3" Voice Coils



D663A	6-1/2" Convertible with Aluminum Tweeters
D663S	6-1/2" Convertible with Silk Tweeters
D693A	6 x 9" Convertible with Aluminum Tweeters
D693S	6 x 9" Convertible with Silk Tweeters

- Convertible Design - Component or Coaxial Use
- Hard Anodized Aluminum Cone
- Rubber Surround
- High Density Proprietary Composite Frame
- Flat Progressive Spider
- Inductively Controlled Motor Design
- Rubber Boot Magnet Protector
- Model Specific Crossovers

D3 SERIES


D308D4	8" Dual 4Ω Voice Coil • 200 Watts RMS
D310D2.2	10" Dual 2Ω Voice Coil • 400 Watts RMS
D310D4.2	10" Dual 4Ω Voice Coil • 400 Watts RMS
D312D2.2	12" Dual 2Ω Voice Coil • 400 Watts RMS
D312D4.2	12" Dual 4Ω Voice Coil • 400 Watts RMS
D315D2.2	15" Dual 2Ω Voice Coil • 500 Watts RMS
D315D4.2	15" Dual 4Ω Voice Coil • 500 Watts RMS

- Textured Copolymer Cone w/ Aluminum Dust Cap
- Nitrile Butadine Rubber Surround
- Heavy Gauge Stamped Steel Basket
- Integrated Tinsel Leads
- Venturi Vented Basket & Pole Piece
- 2.5" Voice Coils
- Double Stacked Ferrite Magnet
- Optimized Spider w/ Balanced Linear Suspension



D354i	5-1/4" Coaxials
D364i	6" Coaxials
D344	4" Convertible with Aluminum Tweeters
D364.5	6-1/2" Convertible with Aluminum Tweeters
D374	6 x 8" Convertible with Aluminum Tweeters
D394	6 x 9" Convertible with Aluminum Tweeters
D3TAK	1" Aluminum Tweeter System

- Convertible Design (excl D354i & D364i)
- Textured Copolymer Cones w/ Rubber Surrounds
- Proprietary Composite Frames w/ Shallow Mount
- Flat Progressive Spiders
- Extended Pole Motor Design
- Rubber Boot Magnet Protector
- Aluminum Dome Tweeters w/ Ferro Fluid Cooling
- Model Specific Crossovers

D1 SERIES


D110D2.2	10" Dual 2Ω Voice Coil • 200 Watts RMS
D110D4.2	10" Dual 4Ω Voice Coil • 200 Watts RMS
D112D2.2	12" Dual 2Ω Voice Coil • 250 Watts RMS
D112D4.2	12" Dual 4Ω Voice Coil • 250 Watts RMS

- Titanium Finish IMPP Cone
- Rubber Surround
- Heavy Gauge Stamped Steel Basket
- Long Throw Suspension
- Vented Extended Pole Piece
- 2" Voice Coils
- Ferrite Magnet



D152i	5-1/4" Coaxials
D162.5i	6-1/2" Coaxials
D172i	6 x 8" Coaxials
D192i	6 x 9" Coaxials
D162.5	6-1/2" Component System

- Mica Injected Polypropylene Cone
- Butyl Rubber Surrounds
- Extended Pole Motor Design
- Aluminum Dome Tweeters with Ferro Fluid Cooling
- Model Specific Crossovers
- Shallow Mount



**ONLY AVAILABLE TO AUTHORIZED DEALERS IN
KS, MO, IA, NE AND SOUTHERN ILLINOIS**

HEX PRO SERIES

- TDX Technology (Thermal Dyne eXtreme)
- Proprietary Composite Hex Cone & Aluminum Dust Cap
- Nitrile Butadine Rubber Surrounds
- Die Cast Aluminum Basket
- Integrated Radial Venting
- Dual Progressive Poly Aramid Composite Fiber Spiders
- Vented Pole Piece
- Ultra High Energy Neodymium Magnet
- Dual 2Ω Voice Coils (3" / 3-1/2")

HP10	10" Dual 2Ω Voice Coil • 600 Watts RMS
HP12	12" Dual 2Ω Voice Coil • 800 Watts RMS



- TDX Technology (Thermal Dyne eXtreme)
- Proprietary Kevlar/Nomex HEX Cone
- Butyl Rubber Surrounds
- Nomex Spider with Embedded Lead Wires
- Die Cast Aluminum Frame
- Ultra High Energy Neodymium Magnet
- 30mm Polymer Treated Alloy Tweeter
- Precision Matched Programmable Crossovers

HP650	6-1/2" Components with Aluminum Tweeter
--------------	---



HEX SERIES

- Carbon Fiber Cone
- Neodymium Motor
- Butyl Rubber Surround
- Cast Aluminum Basket
- S124: 3" Voice Coil & 3.1" Depth
- S104: 2" Voice Coil & 2.7" Depth

S10.4	10" Single 4Ω Voice Coil • 150 Watts RMS
S12.4	12" Single 4Ω Voice Coil • 150 Watts RMS



- Proprietary Kevlar/Nomex HEX Cone
- Butyl Rubber Surrounds
- Flat Progressive Spider with Embedded Lead Wires
- Die Cast Aluminum Frame
- Intercooled Motor Design
- Ferro Fluid Cooled Neodymium Tweeters
- Rear Acoustic Fill Outputs on Crossovers

H500A	5-1/4" Components with Aluminum Tweeters
H500S	5-1/4" Components with Silk Tweeters
H600A	6-1/2" Components with Aluminum Tweeters
H600S	6-1/2" Components with Silk Tweeters



DIAMOND AMPLIFIERS

- PWM MOSFET Switching Power Supply
- Extruded Aluminum Heatsink & Cast End Caps
- RCA Pass Thru
- Nickel Plated RCA, Power & Speaker Connector Block
- Continuously Variable 12dB/Octave Crossovers (24dB/Octave On D600.1 & D1000.1)
- 0-12dB Bass Boost
- Variable Subsonic Filter (Mono Models)
- 0 - 180 Phase Control (Mono Models)
- Remote Level Control (Mono Models)
- Power On & Protection LED
- Thermal Rollback
- Proudly Designed & Engineered In The USA



D400.1	1 x 250w @ 4Ω	1 x 400w @ 2Ω	N/A @ 1Ω
D600.1	1 x 275w @ 4Ω	1 x 450w @ 2Ω	1 x 600w @ 1Ω
D1000.1	1 x 400w @ 4Ω	1 x 700w @ 2Ω	1 x 1100w @ 1Ω
D300.2	2 x 100w @ 4Ω	2 x 150w @ 2Ω	1 x 300w @ 4Ω
D300.4	4 x 50w @ 4Ω	4 x 750w @ 2Ω	2 x 150w @ 4Ω
D600.4	4 x 90w @ 4Ω	4 x 150w @ 2Ω	2 x 300w @ 4Ω