

MULTIMEDIA RECEIVER



DIGITAL BASS PROCESSOR



HEADRESTS W/DVD



6.2" Touchscreen **DVD** Player Bluetooth Built-In Front USB Rear Camera Input Front / Rear / Subwoofer RCA Output

DDX6.2

Double-DIN Multimedia Receiver

Dash Mount Remote Control **PFM Subsonic Filter** Maximum Output Level: 13.5V Frequency Response: 10Hz - 100KHz

DBP1

Bass Restoration Processor

DVD/CD/MP3 Player In Each Headrest A/V Input & Output USB Port & SD Card Reader FM Transmitter & IR Transmitter Remote Control & Game Controller Built In Dual Speakers

HPKG72DVD 7" Headrests w/DVD Player

HPKG92DVD 9" Headrests w/DVD Player

ALL-IN-ONE SAFETY PACKAGE



Front Dash Camera w/HD Recorder Rear License Plate Camera 4 Parking Sensors w/Buzzer Rearview Mirror w/4.3" HD LCD Display 3.7V Rechargeable 500mAh Polymer Battery

EAGLEC4BK 4.3" Mirror / Safety Package

LICENSE PLATE CAMERA



Cast Steel Alloy Frame 2 Backup Sensors w/Proximity Alert 1/4" CCD Color Camera 0.5 LUX Low Light Lens Waterproof Camera Housing 7' Effective Viewing Distance

External Audible Warning Buzzer 130 Viewing Distance 8 IR LEDs For Night Viewing **On-Screen Distance Gauge RCA Video Output Reverse Image**

RCS2IN1B Backup Camera / Sensors







HYDRO AMPLIFIERS



The DS18 Hydro Amplifier Series rugged, compact construction, yet sleek design, SMC (surface mount component) technology, provide its users with trouble free, waterproof (IPX6 Level), amazing sound quality. Engineered for all elements, these amplifiers are a great addition to your marine life including jet skis, boat, etc. as well as a great fit for Jeeps, UTV, ATV Motorsports! The HYDRO micro amplifiers come in 1, 2 and 4 channel stereo options. Also equipped with a removable face plate for setting controls, stainless hardware, and UV/Salt Fog Protection.

NXL6001D	1ch	1 x 250w @ 4Ω 1 x 400w @ 2Ω 1 x 600w @ 1Ω
NXLN1	1ch	1 x 140w @ 4Ω 1 x 230w @ 2Ω 1 x 350w @ 1Ω
NXL2002D	2ch	2 x 100w @ 4Ω 2 x 150w @ 2Ω
NXL4004D	4ch	4 x 100w @ 4Ω 4 x 150w @ 2Ω
NXLN4	4ch	4 x 60w @ 4Ω 4 x 90w @ 2Ω
NXL8005D	5ch	4x80 + 1x200w @ 4Ω 4x125 + 1x300w @ 2Ω

ALL ELEMENT SPEAKERS



Integrated RGB LED Lighting IP65 Marine Grade Specs 100% UV Stable High Temp Injection Molded Composite Basket 25mm Titanium Dome PEI Surround Tweeter

CF65

6-1/2" Coaxials - 125w RMS / 375w Peak

ALL ELEMENT SUBWOOFER



Integrated RGB LED Lighting IP65 Marine Grade Specs 100% UV Stable High Temp Injection Molded Composite Basket

CF10SUB

10" 4 Ω Subwoofer - 300w RMS / 600w Peak

ALL ELEMENT TOWER SPEAKERS



Integrated RGB LED Lighting IP65 Marine Grade Specs RF/BT or WiFi Remote LED Controller UV Compliant High Gloss Composite Body Solid Aluminum 360 Degree Mounting Clamps 1.5", 1.75", 2" NBR Pads Included CF6UTV 6-1/2" Black Carbon Fiber Tower Speake

Injection Molded UV Compliant Polypropylene Cone 1" Titanium Dome PEI Surround Tweeter

CF6UTV	6-1/2" Black Carbon Fiber Tower Speakers - 350w
CF8UTV	8" Black Carbon Fiber Tower Speakers - 425w

MARINE / UTV / JEEP TOWER MOUNT



2.25", 2.5", 2.75", 3" NBR Pads Included Die Cast Solid Aluminum 48.3" - 50.3" Mounting Distance

TSB3B"

Black Tower Mounting Tube







PRO NEODYMIUM RING MIDR	ANGE		
	Red Aluminum Bas Cloth Edge Surrour Non-Pressed Pape Neodymium Magne 3" Mounting Depth	nd r Cone	
and the second s	PRONEO6R	6-1/2" Midrange - 300w RMS / 600w Peak - 4 Ω	SOLD EACH
PRO MIDRANGE			
	Red Aluminum Bas Cloth Edge Surrour Non-Pressed Pape 25oz Ferrite Magne 2.72" Mounting Dep 3.38" Mounting Dep	nd r Cone t th (PRO-X64BM)	
	PROX5.4BM	5-1/4" Midrange - 150w RMS / 300w Peak - 4 Ω	SOLD EACH
	PROX6.4BM	6-1/2" Midrange - 300w RMS / 600w Peak - 4 Ω	SOLD EACH
	PROX8.4BM	8" Midrange - 275w RMS / 550w Peak - 4Ω	SOLD EACH
	PROX8BM	8" Midrange - 275w RMS / 550w Peak - 8Ω	SOLD EACH
PRO COAXIAL	Stamped Steel Bas	ket 3.58" Mounting Depth (PRO-ZT8)	
	Neodymium Magne Cloth Edge Surrour Non-Pressed Pape 1' Neodymium Twe 3.03" Mounting Dep	t id r Cone eter	
	PROZT6	6-1/2" Coaxial - 225w RMS / 450w Peak - 4Ω	SOLD EACH
	PROZT8	8" Coaxial - 275w RMS / 550w Peak - 4Ω	SOLD EACH
PRO 10" MIDBASS			
	Stamped Steel Bas Cloth Edge Surrour Non-Pressed Pape 60oz Ferrite Magne	id r Cone	
Carlo and a second seco	PROX10MBAS	S 10" Midbass - 400w RMS / 800w Peak - 8Ω	SOLD EACH
SPEAKER GRILLS			
	PROGRILL6BL	ACK 6.5" ABS Speaker Grill	
		ACK 8" ABS Speaker Grill	
		• •	
	PROGTW6BK	6.5" RGB ABS Speaker Grill w/1.75 Bullet Tweeter	SOLD EACH
	PROGTW8BK	8" RGB ABS Speaker Grill w/1.75 Bullet Tweeter	SOLD EACH



Last Updated 3/15/19



51



PRO BULLET TWEETER			
	Die Cast Aluminum Impedance: 4 Ohm Sensitivity: 109dB Magnet Size: 14.5o		
	PROTW420	1-3/4" Bullet Tweeter - 275w RMS / 550w Peak - 4Ω	SOLD EACH
PRO BULLET TWEETER			
	PROTW820	1" Bullet Tweeter - 100w RMS / 200w Peak - 4Ω	SOLD EACH
		_	
WRANGLER TAILGATE HOUSI			
	Designed For Jeep	Illow Subwoofers (SOLD SEPERATELY) JK/JKU/JL Tailgate Applications For RGB & Speakers	
	JBASS	JK/JL Wrangler Tailgate Housing	
AMPLIFIED BASS PACKAGES			
1000	Built-In Class A/B A Carbon Fiber Vinyl Includes 8ga Ampli	Wrap	
	BPX110A	Single 10" Amplified Bass Enclosure	
	BPX112A	Single 12" Amplified Bass Enclosure	
2	BPX212A	Dual 12" Amplified Bass Enclosure	









ELITE Z-SERIES SUBWOOFERS



Kevlar Dustcap Black Steel Basket Paper Cone & Foam Surround BASV 4 Layer Voicecoil

6" Dual 4 Ω Subwoofer - 300w RMS / 600w Peak
8" Dual 4 Ω Subwoofer - 500w RMS / 900w Peak
10" Dual 4 Ω Subwoofer - 750w RMS / 1500w Peak
12" Dual 4 Ω Subwoofer - 800w RMS / 1600w Peak

SHALLOW MOUNT SUBWOOFERS



Designed For Small And Tight Applications 50oz Ferrite Magnet Aluminum Frame Paper Cone Rubber Surround BASV 4 Layer Voice Coil		3.5" Mounting Depth (SW10S4) 3.7" Mounting Depth (SW12S4)	
SW10S4	10" 4Ω Subwoofer - 500w	/ RMS / 1000w Peak	
SW12S4	12" 4Ω Subwoofer - 500w	/ RMS / 1000w Peak	

GEN-X SUBWOOFERS



GENX104D	10" Dual 4 Ω Subwoofer - 400w RMS / 800w Peak
GENX124D	12" Dual 4 Ω Subwoofer - 450w RMS / 900w Peak

SELECT SUBWOOFERS



Steel Frame Basket Foam Edge Surround Paper / Glass Fiber Cone 45oz Ferrite Magnet 5.47" Mounting Depth

SLC10S	10" 4Ω Subwoofer - 220w RMS / 4400w Peak
SLC12S	12" 4 Ω Subwoofer - 250w RMS / 500w Peak







EXL 3 OHM SPEAKERS



518

Black Glass Fiber Cone w/Rubber Surround Advanced PEI Dome Neodymium Tweeter Die Cast Basket w/Machined Finish 1" BASV Voice Coil 3 Ohm Impedance Strontium Magnet

EXLSQ5.25	5-1/4" Coaxials - 80w RMS / 340w Peak - 3Ω
EXLSQ6.5	6-1/2" Coaxials - 120w RMS / 400w Peak - 3Ω
EXLSQ6.9	6 x 9" Coaxials - 160w RMS / 560w Peak - 3 Ω
EXLSQ65C	6-1/2" Components - 120w RMS / 400w Peak - 4Ω



GEN-X SPEAKERS



Black Paper Cone w/Rubber Surround Mylar Dome Tweeter Stamped Steel Basket 1" ASV Voice Coil 4 Ohm Impedance

GENX4	4" Coaxials - 40w RMS / 120w Peak - 4Ω
GENX525	5-1/4" Coaxials - 45w RMS / 135w Peak - 4 Ω
GENX65	6-1/2" Coaxials - 50w RMS / 150w Peak - 4 Ω
GENX46	4 x 6" Coaxials - 45w RMS / 135w Peak - 4 Ω
GENX57	5 x 7" 3-Way Coaxials - 50w RMS / 165w Peak - 4 Ω
GENX69	6 x 9" 4-Way Coaxials - 60w RMS / 180w Peak - 4 Ω
GENX65C	6-1/2" Components - 50w RMS / 150w Peak - 4 Ω

TWEETERS



TWC

1" Silk Dome Tweeters - 20w RMS / 60w Peak







EXL SOUND Q FULL RANGE AMPLIFIERS



The people who live and breathe car audio demanded a higher-performing, extremely intelligent (technologically speaking), dynamic product line. With their compact size and new SMC (surface, mount component) technology, the EXL SQ amplifiers are the epitome of competition and sound quality amplifiers all in one sleek design. Boasting audio precision quality control verification and Tiffany RCA jacks, these amplifiers offer high quality audio reproduction for the audiophile and everyday listener alike. This line has built in LEDs that light up for power/protection/clipping and have the latest Class-D circuit design.

EXLSQ1600.1D	1ch	1 x 700w @ 4Ω	1 x 1120w @ 2Ω	1 x 1600w @ 1Ω
EXLSQ600.1D	1ch	1 x 250w @ 4Ω	1 x 400w @ 2Ω	1 x 600w @ 1Ω
EXLSQ1000.1D	1ch	1 x 440w @ 4Ω	1 x 730w @ 2Ω	1 x 1000w @ 1Ω
EXLSQ600.2	2ch	2 x 300w @ 4Ω	2 x 420w @ 2Ω	1 x 840w @ 4Ω
EXLSQ320.4	4ch	4 x 80w @ 4Ω	4 x 125w @ 2Ω	2 x 250w @ 4Ω
EXLSQ1000.4	4ch	4 x 250w @ 4Ω	4 x 500w @ 2Ω	2 x 720w @ 4Ω

CANDY AMPLIFIERS



RMS Power Ratings Shown

CANDYXXL1B	1ch	1 x 400w @ 4Ω 1 x 650w @ 2Ω 1 x 1000w @ 1Ω
CANDYX1B	1ch	1 x 240w @ 4Ω 1 x 400w @ 2Ω 1 x 600w @ 1Ω
CANDYX4B	4ch	4 x 80w @ 4Ω 4 x 120w @ 2Ω
CANDYX5B	5ch	4x80 + 1x200w @ 4Ω 4x120 + 1x320w @ 2Ω

EXL SOUND QUALITY AMPLIFIERS



Class D SMC Technology Power/Protection/Clipping Indicators RMS Power Ratings Shown

EXLSQ1200.2 2ch $2 \times 600 \text{ w} @ 4\Omega$ $2 \times 850 \text{ w} @ 2\Omega$ $1 \times 1700 \text{ w} @ 4\Omega$

AMP INSTALL KITS



17' 4ga Red Super Flex Twist Premium Power Cable
3' 4ga Black Super Flex Twist Premium Ground Cable
17' 14ga Red/Black Super Flex Twist Premium Speaker Cable
17' 2ch Shielded Twisted Pair Premium Audio Interconnects
17' Remote Turn On Wire w/Split Loom Tubing
AGU Fuseholder & 100A AGU Fuse

AMPKIT4 4ga Amp Install Kit









Includes Switches, Wire Harness, Adapters

RCPWK4D

1-Way Alarm System

4D Universal 4DR Power Window Kit w/Switches

CAR ALARMS



2) 4-Button Long Distance Transmitters 6 Tone 125dB Siren Shock Sensor w/Sensitivity Adjustment Remote Trunk Release Parking Light Flash & Engine Cut Off **18SPORT** 1-Way Alarm System

TRIPLE HORNS



Up To 125dB Output 100% Stainless Steel Horns Max Pressure: 150 PSI Max Current: 6.5A Horn Size: 16.34" x 14.17" x 11.81" Compressor Size: 6.7" x 3.54" x 6.3"

TH3COMBO Train Horns w/1.5 Gallon Air Compressor

FOLDABLE BLUETOOTH HEADPHONES



Foldable Bluetooth Headphone TF Card FM Radio AUX Input 2hr Charge Time, 4hr Play Time Sweat Resistant Comfortable & Secure Fit Built In Microphone

HDPBT

Foldable Bluetooth Headphone



56





VJ LED HEADLIGHT BULB CONVERSIONS



Solid Beam Pattern 6500K Light Temperature CSP LED Chip Technology Canbus Decoders May Be Required To Fix Blinking Or Error Codes

VJH1	H1 6K LED Conversion Kit
VJH3	H3 6K LED Conversion Kit
VJH4	H4 6K LED Conversion Kit
VJH7	H7 6K LED Conversion Kit
VJH10	H10 6K LED Conversion Kit
VJH11	H11 6K LED Conversion Kit
VJH13	H13 6K LED Conversion Kit
VJ880	880 6K LED Conversion Kit
VJ5202	5202 6K LED Conversion Kit
VJ9004	9004 6K LED Conversion Kit
VJ9005	9005 6K LED Conversion Kit
VJ9006	9006 6K LED Conversion Kit
VJ9007	9007 6K LED Conversion Kit

200A AUTOMATIC BATTERY CHARGER



Input (Automatic Bi-Volt): 90 to 140Vac / 170 to 240Vac Consumption at Max Load: 3000W Maximum Output Current: 200 Amperes Maximum Output Voltage: 14.4 Vdc Intelligent Charging System: 13.8 / 14.4 Vdc Cyclic Digital Display To Monitor Voltage Or Current LED Battery Level Indicators Cooling Fan Excess Charge, Short On Output, And Thermal Protection

PWSI200A

200A Automatic Battery Charger

INFINITE CAR JUMP STARTER



ATS10K Specifications:

10000mAh Capacity High Power SOS LED Flashlight W/Strobe USB Charging Port Up To 2A Car Jump Start Output: 12V Start Current: 200A Peak Current: 400A Charge Time: 4 Hours

ATS18K Specifications:

18000mAh Capacity High Power SOS LED Flashlight W/Strobe USB Charging Port Up To 2A Quick Charge Output: 9V / 2A 5V / 3A QC 3.0 Car Jump Start Output: 12V Start Current: 200A Peak Current: 400A Charge Time: 6 Hours Includes Home & Car Adapter, Carry Bag

ATS10K	10000mAh Jump Starter
ATS18K	18000mAh Jump Starter





AUDISON BIT DMI



audison

AUDISON BIT ONE HD



AUDISON BIT NOVE



Digital interface for MOST systems Provides the ability to connect Audison bit processors and amplifiers equipped with digital input to OEM systems featuring MOST technology Voltage: 8 - 18 VDC Automatic turn on / off via MOST Remote 12 VDC output MOST optical input TOSLINK optical output USB PC connection

BITDMI Digital Interface for MOST Systems

Hi-Res audio for studio master quality in your car Improved acoustic quality with crossover filters and FIR equalizers SHARC series Hi-End Analog Device Processor Cirrus Logic A/D - D/A converters 12 analog inputs 2 stereo auxiliary inputs 2 optical digital inputs 13 output channels (analog RCA & digital AD LINK) Advanced PC software (USB connection) De-equalization recreates a flattened signal 3 equalizers based on 2 types of filters (FIR & IIR) 5 parametric poles main equalization (FIR type) Digital time delay Powered by bit Drive technology Auto tuning with Audison bit Tune Includes DRC MP controller

BITONEHD 13ch Hi-Res Digital Audio Processor with DRC MP Controller

6 high level / low level inputs
1 stereo auxiliary input
2 optical digital inputs
USS Universal Speaker Simulator technology
Advanced PC software (USB connection)
De-equalization recreates a flattened signal
9 pre out analog outputs

10 pole parametric equalizer 68 step electronic crossover Digital time delay Powered by bit Drive technology iDatalink Maestro AR compatibility Includes DRC MP controller

BITNOVEDRC Sound Processor with DRC MP Controller

AUDISON ADAPTER CABLES



ADS-MAR-AUD Audison Adapter Cables for Maestro AR to PRIMA Amplifier ADS-MAR-AUD2 Audison Adapter Cables for Maestro AR to Bit Nove



58



audison

AUDISON VOCE AMPLIFIER



AUDISON FORZA AMPLIFIER



5ch hybrid design 2) AB Class output (2 x 250w RMS 4Ω) 2) A Class outputs (2 x 75w RMS 4Ω) 1) D Class output (1 x 1000w RMS 2Ω) LED status display Flexible filters for versatile configurations

Top mount control panel Unparalleled efficiency Sub volume remote 2 gauge power and ground connections Digital-Link compatible

ΑV5.1K 2 x 250w + 2 x 75w RMS @ 4Ω + 1 x 1000w RMS @ 2Ω

High power 8 channel amplifier 9 channel built-in processor Guided setup for input level and de-equalization 7 pre-configured DSP presets 9th channel pre-out for mono amp or active sub Optical S/PDIF digital input 4V RMS RCA pre-out Linkwitz @ 12/24 dB / Butterworth 6/12/18/24 dB Phase Control Parametric equalizers Time alignment Micro USB PC connection

APF8.9BIT 8 x 85W @ 4Ω / 8 x 130W @ 2Ω

AUDISON VOCE SERIES



Cotton fiber pressed paper cone Tetolon fiber dome tweeters Butyl rubber surround

F

AVX6.5	6.5" Voce 2-Way Coaxial - 200w Peak
AV6.5	6.5" Voce Woofer - 200w Peak
AV3.0	3" Voce Midrange - 100w Peak
AV1.1	28mm Voce Tweeter - 180w Peak

AUDISON LOADED ENCLOSURE



Reflex loading	8" Single 4 ohm voicecoil
Tuned to concentrate SPL in the lowest frequency	Low resonant frequency
range	

APBX8R 8" 4Ω Loaded Enclosure - 500w Peak



