

The Original Firestik

The most popular wire-wound CB antenna in the world. A proven performer since 1975. The loading coil on "KW" antennas is easily accessible. Will also receive the NOAA weather frequencies.

100% American made with 100% American materials. Custom blended, glass fiber reinforced shaft. Wound with heavy insulated copper wire to prevent oxidation and shorted windings.

KW2 (B/R/W)

2' 5/8wv 100 Watts.

KW3 (B/R/W)

3' 5/8wv 300 Watts.

KW4 (B/R/W)

4' 5/8wv 400 Watts.

KW5 (B/R)

5' 5/8wv 500 Watts.

Firestik II

Same as KW Series, but with bare-hands tuneable tip! (Black/Red/White).

FS2 (B/R/W)

2' 5/8wv 300 Watts.

FS3 (B/R/W)

3' 5/8wv 650 Watts.

FS4 (B/R/W)

4' 5/8wv 900 Watts.

FS5 (B/R/W)

5' 5/8wv 1000 Watts.

Co-Phase Harnesses

K9 18' - PL to Lug

K9A 18' - PL to PL259's

72 Ohm RG58A/U coaxial.

Magnet Mount

K11

Macho Magnet Mount - 4-5/16" magnet, low profile, with 18' coax.

Mounts / Accessories

K4

Heavy Duty Stud Mount - With Lug connector.

K4A

Heavy Duty Stud Mount - With S0239 connector.

K24

Heavy Duty Side Mount w/S0239 - For whips up to 5'.

M2

Molded Side Mount - With lug connector. Coax connection made on inside of vehicle for custom look.



Mounts / Accessories (cont.)

R3M Med. Duty - plated

R3H Heavy Duty - plated

Shock Springs - Protects antenna/mount/vehicle. Use R-3M for antennas up to 3ft; R-3H for antennas up to 5ft.

K1A

Quick Disconnect - 3/8 x 24 threaded. Prevents theft, internal locking mechanism, heavy chrome-plated brass. New stainless steel locking pin.

Stainless Steel Mounting Brackets

SS194 Crimp-On

SS194A Screw-On

Extended Stake Hole Mounts - Extends out over bed rail to allow use with camper shell. Stainless steel.

SSF4A Screw-On

Flat Bracket - 2" x 5", Stainless steel.

SS174 2" Deep Lip

Hood / Trunk Channel Mount - Fits inside channel with no holes. Stainless Steel.

SS184 Crimp-On

SS184A Screw-On

Ram/Dakota Hood or Flat Edge Mounts - May be used for any horizontal flat edge. Stainless Steel.

SS134A Screw-On

Clamp On Flat Mounts - No hole installation on flat side-view mirror arm supports. Stainless Steel.

SS124 Crimp-On

SS124A Screw-On

Stainless Steel 1" x 4" Flat Mounts

SS3M Medium Duty

SS3H Heavy Duty

3/8 x 24 Stainless Steel Springs

SS64A S0239

3-Way Mounting Brackets - Horizontal or Vertical rails or mirror brackets.

Stainless Steel Mounting Kits

MK184R

Ram/Dakota Hood or Flat Edge Mini-Kit - With 18' Fire-Flex coax.