HIFONICS ALPHA AMPLIFIERS



HIFONICS ALPHA SPEAKERS

HIFONICS ALPHA SUBWOOFERS

(C)	
-	-
-	

• Ultra-Fi™ MOSFET - high power with minimal distortion

HIFONICS POWER FROM THE GODS

- T3 (Twin Turbo Toroid) power supply torroids
- Pulse Width Modulated MOSFET Power supply
- Low Noise Pre-Amp Circuitry

Low Noise Pre-Amp Circuitry			Overload & Speaker Short Protection		
A3000.1D	1 x 750w @ 4Ω	1 x 1500w @ 2Ω	1 x 3000w @ 1Ω		
A2000.1D	1 x 500w @ 4Ω	1 x 1000w @ 2Ω	1 x 1500w @ 1Ω		
A1200.4D	4 x 150w @ 4Ω	4 x 300w @ 2Ω	2 x 600w @ 4Ω		
A2500.5D	4 x 60w + 1 x 25	50 @ 4Ω 4 x 100)w + 1 x 650 @ 2Ω		

- Aluminum Dome Tweeters
- Polypropylene Cone w/Butyl Rubber Surround
- High Temperature Surround Adhesive
- Textured ABS Gasket
- Heavy Gauge Progressive Die Stamped Steel Frame

Woven Glass Fiber Cone w/Integrated Dust Cap

HA65CX	6-1/2" Coaxials • 300W Max / 150W RMS
HA69CX	6" x 9" Coaxials • 400W Max / 200W RMS
HA5768CX	5"x7" / 6"x8" Coaxials • 250W Max / 125W RMS

- Ferrite Magnet
- Pure Copper Voice Coil
- Kapton Voice Coil Former

Accu-Cross Crossovers

• Includes Illuminated Bass Remote

• Illuminated Logo and Angled Output Connectors

Over-Coil Cooling System

Front & Rear Venting

• Grills Included (HA65CX / HA69CX)

	0		0
 UV Rubber Surround 		Poly Cotton Spider	
 Nickel Plated Terminals 			
• High Temperature Voice Coil &	Former		

- Vented Aluminum Former
- HAW15D4 15" Dual 4 Ω Subwoofer • 1400W Max / 700W RMS **HAW12D4** 12" Dual 4 Ω Subwoofer • 1200W Max / 600W RMS HAW10D4 10" Dual 4 Ω Subwoofer • 1000W Max / 500W RMS

HIFONICS THOR POWERSPORTS SOUND BARS



- Large Controls For Easy Operation
- Map/Reading Light
- Solid Aluminum Structure
- Heavy Impact Grill
- TPS6 6 Speaker Sound Bar

TPS10 10 Speaker Sound Bar

- High Efficiency Drivers For Bass & Midrange
- Titanium Dome Tweeters With Neodymium Magnets
- Bluetooth Or 3.5mm Input
- 2V Audio Output
- Auto Shutoff

DASH MOUNT USB & 3.5MM INPUT



PSAP2S Dash Mount USB & 3.5mm Input with RCA & USB Extension Cable



Last Updated 3/15/19



MAXXSONICS

MBQUART

1B QUART 160W POWERED BLUETOOTH AM/F



- Bluetooth Connect & Quick-Pair
 - 4V Front / Rear / Sub RCA Preamp outputs
 - 4 Channels with 40 watts of output (160w total)
 - Dual audio zone capability
 - 3.5" High contrast LED screen

· Easily connect to Bluetooth devices · Designed with a powerful tuner section

• 2V RCA Preamp outputs

Marine / Power Sports Source Unit w/Bluetooth

- External camera input
- IPX67 tested to be waterproof, dustproof and UV stable
- RCA auxiliary input
- Rear USB port

- GMRLED
- - · Splash and dust proof LCD Display
- Apple® Control
- · RCA auxiliary input
- Rear USB port
- 3.125" "Gauge Mount"



GMR2.5 Gauge Mount Source Unit w/Bluetooth

• IPX67 tested to be waterproof, dustproof and UV stable

• 4 Channels with 40 watts of output (160w total)



PSAP2 Dash Mount USB & 3.5mm Input with RCA & USB Extension Cable



Proprietary	full	range	Class	D	design	
riophotary	run	runge	01033		ucoign	

- Small footprint ideal for challenging installations
- Detachable wire harness simplifies installation
- · Life Shield designed and tested against the elements
- Equalization and bass boost controls
- · Sealed and removeable system connections
- ABYC & ASTM certified conformal coated PC boards to resist corrosion from salt spray & moisture
- Mono and 5ch models include bass remote

	iu bass boost contro	15
NA2 400.1	1 x 200w @ 4Ω	1 x 400w @ 2Ω
NA2 400.2	2 x 125w @ 4Ω	2 x 250w @ 2Ω
NA2 320.4	4 x 40w @ 4Ω	4 x 80w @ 2Ω
NA2 500.5	4x40w + 1x100 @	4Ω 4x80w + 1x200 @ 2Ω

143 CA IPACT ele:RS

IMAGE NOT AVAILABLE AT PRESS TIME

- Full Range Class D Technology
- IPX65 Certified
- Top Mount Controls

NA3 560.4 4 x 70W RMS @ 4Ω 4 x 140W RMS @ 2Ω NA3 1000.5 $4x60W + 1x350W \ \text{RMS} @ 4\Omega \quad 4x __W + 1x __W \ \text{RMS} @ 2\Omega$ NA3 600.6 6 x 50W RMS @ 4Ω 6 x ____ _W @ 2Ω



Last Updated 3/15/19



MBQUART

MAXXSONICS

MB QUART POLARIS RZR AUDIO UPGRADE



- GMR-3 Gauge Mount Radio w/Bluetooth
- RZR-DASHR RZR Radio Mount
- PSAP-2 Dash Mount USB & Aux Input Plug
- NA2-400.2 400w 2ch Powersports Amplifier
- NA2-400.1 400w Powersports Subwoofer Amplifier
- RZR-AMPD RZR Dual Amp Rack
- RZR-RDAH RZR Radio & Dual Amp Harness
- NH1-120B 8" Coaxial Compression Horn Speakers
- RZR-POD8 Front Speaker Enclosures
- FW1-254 10" Formula Subwoofer
- RZR-SUB10 Ported Under-Dash Subwoofer Enclosure
- NHT1-120B 8" Cage Mount 2-Way Compression Horns
- SWVL-1B Swivel Mount Brackets For Rear Pods

MBQSTG51	5 Speaker Audio Upgrade Kit for Polaris RZR - Includes rear cage mount speakers
MBQSTG31	3 Speaker Audio Upgrade Kit for Polaris RZR - Does <u>NOT</u> include rear cage mount speakers

MB QUART POWERSPORTS SPEAKERS





- Pure titanium compression diaphragm / tweeter
- Butyl rubber surround
- Composite poly cone
- High temperature voice coil and kapton former
- Front and rear vent cooling
- 12dB Butterworth crossover
- Composite ABS and glass fiber frame
- High energy strontium ferrite magnet
- UV Treated and IPX67 rated

- Injection molded enclosure w/steel reinforced mountingCentering ring
- Die cast mounting hardware 1.5" to 2.75"
- LED lighting with limitless color choices (select models)
 Limitless color choices with color on, off, strobe and pro-
- grammed "light shows" possible. Optional N1-RC required for control of lighting systems and to sync multiple illuminated speakers. Pre-programmed demo mode included on all lighted systems.

•	D G	•	G
	D (

NHT1C116LB	6.5" Powersports Speakers w/LED Illumination (Black) • 150w Max
SWVL1B	180 Degree Swivel Bracket For NT1, NT2, NHT1 Speakers
N1RC	Wireless RF Controller for LED Illumination

MB OUART NAUTIC PREMIUM SPEAKERS



 Interchangeable Black/White/Silver Grill 	s
--	---



Y30 Strontium Ferrite Magnet

MB QUART NAUTIC PREMIUM SUBWOOFERS



- IPX68, CEA426B Certifications
- UVA protected water resistant composite polypropylene
 Gold Plated Push Terminals cone with NBR rubber surround
- Lightweight Fiber Reinforced Composite Frame
- High Energy Motor Assembly

NPW254 12" 4Ω Subwoofer • ____W Max / ____W RMS



Last Updated 3/15/19

