

BRUTUS AMPLIFIERS



Features: High Efficiency Super Digital D-Class Technology, 4/2/1 Ohm Stable, Bass EQ With 45Hz Bass Boost, Variable Low Pass, Subsonic Filter, Phase Shift & Level Control, Balanced Line Input, Illuminated Logo Bass Remote Included.

BRZ1200.1D	1 x 450w @ 4Ω / 1 x 900w @ 2Ω / 1 x 1200w @ 1Ω
BRZ1700.1D	1 x 600w @ 4Ω / 1 x 1200w @ 2Ω / 1 x 1700w @ 1Ω
BRZ2100.1D	1 x 700w @ 4Ω / 1 x 1400w @ 2Ω / 1 x 2100w @ 1Ω
BRZ2400.1D	1 x 850w @ 4Ω / 1 x 1700w @ 2Ω / 1 x 2400w @ 1Ω

HF AMPLIFIERS



Features: A/B Analog Class, Blue Military Grade PCB, 4/2 Ohm Stable, High Speed MOSFET Output Devices, PWM Power Supply, Variable Crossovers, Illuminated HF Logo.

HFi1000	1 x 475w @ 4Ω / 1 x 750w @ 2Ω / 1 x 1000w @ 1Ω
HFi1500	1 x 500w @ 4Ω / 1 x 1000w @ 2Ω / 1 x 1500w @ 1Ω
HFi2000	1 x 650w @ 4Ω / 1 x 1300w @ 2Ω / 1 x 2000w @ 1Ω
HFi2500	1 x 850w @ 4Ω / 1 x 1700w @ 2Ω / 1 x 2500w @ 1Ω
HFi100.2	2 x 100w @ 4Ω / 2 x 200w @ 2Ω / 1 x 400w @ 4Ω
HFi55.4	4 x 55w @ 4Ω / 4 x 110w @ 2Ω / 2 x 220w @ 4Ω
HFi100.4	4 x 100w @ 4Ω / 4 x 200w @ 2Ω / 2 x 400w @ 4Ω

ZEUS AMPLIFIERS



Features: A/B Analog Class, 4/2 Ohm Stable, Bass EQ w/45Hz Bass Boost & 0-10dB Control, High Speed MOSFET Output Devices, PWM Power Supply, Variable Crossovers, Illuminated Logo, Bass Remote Included On 2, 4 & 5ch Amplifiers.

ZXi200.2	2 x 200w @ 4Ω / 2 x 400w @ 2Ω / 1 x 800w @ 4Ω
ZXi40.4	4 x 40w @ 4Ω / 4 x 80w @ 2Ω / 2 x 160w @ 4Ω
ZXi80.4	4 x 80w @ 4Ω / 4 x 160w @ 2Ω / 2 x 320w @ 4Ω
ZXi150.4	4 x 150w @ 4Ω / 4 x 300w @ 2Ω / 2 x 600w @ 4Ω
ZXi60.4+1K	4 x 60w + 1 x 475w @ 4Ω / 4 x 120w + 1 x 750w @ 2Ω

AMP BRIDGING MODULE



Permits Interconnecting Of Up To 5 Amplifier Pairs Into A Master and Slave Configuration. Remote Mounted Level Control w/Clipping Indicator. Features: 24dB Low Pass Filter, Subsonic Filter, Phase Control, Parametric Bass EQ, Chrome Finish.

MLX100	Amp Bridging Module w/Remote Level Control
---------------	--

3-WAY CROSSOVER



8.5v Line Driver, 2ch or 4ch Operation, 2-Way or 3-Way Operation, Direct Sub Input, Dash Mountable 0-12dB Bass Boost, Phase Shift, Line Output.

HFXR	3-Way Crossover w/8.5V Output
-------------	-------------------------------

4 BAND EQ / 3-WAY CROSSOVER



1/2 DIN ISO Mount Chassis, 4 Band EQ w/18dB Variable 9v Preamp Output, Master Volume & Sub Control, Front/Rear Fader, 2 Audio Inputs, 12dB High Pass/Low Pass Filters.

HFEQ	4 Band EQ w/9V Output
-------------	-----------------------

BRUTUS SUBWOOFERS



Features Include: Black Stamped Steel Frame, For Ported Or Sealed Applications, 4 Layer High Temp 2.5" Aluminum VC Assembly, High Excursion Rubber Surround, Dual Flat Nomex Spider Material, Nickel Plated Push Wire Terminals.

BRZ12D4 12" Dual 4Ω Voice Coil Sub - 600w RMS/1200w MAXX

BRZ15D4 15" Dual 4Ω Voice Coil Sub - 700w RMS/1400w MAXX

BRZ12SQD4 12" Dual 4Ω Voice Coil Sub - 600w RMS/1200w MAXX

ZEUS SUBWOOFERS



Features Include: Polypropylene One Piece Cone & Dust Cap, Rubber Surround, Ultra Rigid Stamped Steel Basket, Rubber Magnet Wrap, Nickel Plated Spring Loaded Terminals, Designed For Sealed And Ported Enclosures.

ZX12D2 12" Dual 2Ω Voice Coil Sub - 500w RMS/1000w MAXX

ZX12D4 12" Dual 4Ω Voice Coil Sub - 500w RMS/1000w MAXX

HIFONICS SUBWOOFERS



Features Include: High Energy Magnet, Black Polypropylene Cone, Chrome Basket, Multi Layer High-Temp Voice Coil, Integrated Spider Tinsel Lead, High Excursion Rubber Surround, Suitable For Ported Or Sealed Enclosures.

HF12D4 12" Dual 4Ω Voice Coil Sub - 300w RMS/600w MAXX

HIFONICS SPEAKERS



Features Include: Polypropylene Speaker Cone, Moisture Resistant Rubber Surround, Anti Resonant Stamped Steel Basket, Neo Mylar Soft Dome Tweeter, Impact Resistant Speaker Elements, High Mid-Bass Impact, Wide Nominal Power Range

HF16.5C 6-1/2" Components - 30-100w RMS

HF165CX 6-1/2" 2-Way - 30-65w RMS

HF169CX 6 x 9" 2-Way - 30-110w RMS

ZEUS SPEAKERS



Features Include: Low Profile Anti Resonant MaxxFitt Titanium Chromed Speaker Frames, Sound Light Speaker Illumination, 12mm Neodymium Silk Dome Tweeters, Ceramic Titanium Composite Cones, Butyl Rubber Surrounds.

ZXi6.5C 6-1/2" Components - 30-100w RMS/500w MAXX

ZXi63 6-1/2" 3-Way - 30-75w RMS/375w MAXX

ZXi683 6 x 8" 3-Way - 30-85w RMS/425w MAXX

ZXi693 6 x 9" 3-Way - 30-110w RMS/550w MAXX