

VOLT SERIES AMPLIFIERS



- A/B Analog Class
- Advanced Protection for Ultra Reliability
- High Level Input Jack for OEM Integration Without Additional Hardware
- Bass Boost
- 24dB High/Low Pass Crossovers
- Dual Sided Mil Spec PCB's

V1000.1	1 x 500w RMS	1 x 1000w MAX
V500.2	2 x 125w RMS	2 x 500w MAX
V1000.4	4 x 125w RMS	2 x 500w MAX

NANO BLOCK AMPLIFIERS



- Extreme Power In A Small Footprint
- Ultimate Mounting Flexibility
- 1 Ohm Stable Design (Mono Amps)
- Mil Spec Double Sided PCB w/SMD Parts
- Built In Noise Reduction Circuitry
- Full MOS-FET Switching Devices
- Adjustable Hi/Lo 24dB Crossovers
- 0 / 6dB / 12dB Bass Boost (Mono Amps)
- 24dB Subharmonic Filter (Mono Amps)
- Next-Gen Advanced Protection Circuitry
- Worldwide Standards Compliant (CEA-2006, CE, E-mark, RoSH)

N2	1 x 200 RMS @ 4Ω	1 x 400 RMS @ 2Ω	1 x 800 RMS @ 1Ω
N3	1 x 450 RMS @ 4Ω	1 x 700 RMS @ 2Ω	1 x 1400 RMS @ 1Ω
N4	1 x 650 RMS @ 4Ω	1 x 1000 RMS @ 2Ω	1 x 2000 RMS @ 1Ω
NX2	2 x 120 RMS @ 4Ω	2 x 240 RMS @ 2Ω	1 x 480 RMS @ 4Ω
NX3	2 x 120 + 1 x 800 RMS @ 4Ω		
NX4	4 x 100 RMS @ 4Ω	4 x 200 RMS @ 2Ω	2 x 400 RMS @ 4Ω
NX5	4 x 120 + 1 x 300 RMS @ 4Ω	4 x 220 + 1 x 500 RMS @ 2Ω	

DIGITAL BLOCK AMPLIFIERS



- Low Pass 18dB Crossovers
- 30Hz - 80Hz Adjustable Parametric Bass EQ with (+) 12dB Gain
- Proprietary Bass Kompressor Circuitry
- Adjustable Low Pass 18dB Subharmonic Filter
- Short Circuit, Thermal, Reverse Voltage & Over Voltage Protection
- Heavy Duty Power Supply
- Heavy Duty Aluminum Heatsink
- Illuminated Logo
- Designed & Engineered In The USA
- 1 Ohm Stable Design (Mono Amps)

D1200	1 x 250 RMS @ 4Ω	1 x 450 RMS @ 2Ω	1 x 600 RMS @ 1Ω
D2400	1 x 350 RMS @ 4Ω	1 x 650 RMS @ 2Ω	1 x 1200 RMS @ 1Ω
D3600	1 x 650 RMS @ 4Ω	1 x 950 RMS @ 2Ω	1 x 800 RMS @ 1Ω
D800.4	4 x 120 RMS @ 4Ω	4 x 480 RMS @ 2Ω	

SUBWOOFER ENCLOSURES



- 3/4" MDF Construction with Dual Layered 1.2" MDF Face Plate
- Carpeted With Custom Embroidered Massive Logo
- Sloped Back Wall Design
- Mass Mat Sound Damping Technology
- Heavy Gauge Metal Speaker Protection Rods
- Custom Tuned Dual Flare Ports
- 5-Way Binding Post Push Typer Terminal
- 12" 600w Max Power CEA 2006 Compliant Subwoofer

VB12	12" Single Subwoofer Enclosure	• 300w RMS / 600w Peak
VBD12	12" Dual Subwoofer Enclosure	• 600w RMS / 1200w Peak

DC SERIES SUBWOOFERS



- Kevlar/Glass Fiber "Finger Cut" Cone
- 1" Tall Santoprene Surround
- Push-Pin or Banana Terminals
- Woven Silver Plated Tinsel Leads
- Powder Coated Aluminum Cast Basket
- 120oz Flux Ferrite Y40 Magnet
- 40mm Peak to Peak X-Max
- Dual 2.5" 4 Ohm Voice Coils

DC10	10" Dual 4Ω V.C.	• 600w/1200w
DC12	12" Dual 4Ω V.C.	• 600w/1200w
DC15	15" Dual 4Ω V.C.	• 600w/1200w

TW SERIES SUBWOOFERS



- Kevlar/Glass Fiber "Finger Cut" Cone
- 1" Tall Santoprene Surround
- Push-Pin or Banana Terminals
- Woven Silver Plated Tinsel Leads
- Powder Coated Aluminum Cast Basket
- 80oz Flux Ferrite Y40 Magnet
- 24mm Peak to Peak X-Max
- Dual 2.5" 4 Ohm Voice Coils

TW10	10" Dual 4Ω V.C.	• 500w/1000w
TW12	12" Dual 4Ω V.C.	• 500w/1000w
TW15	15" Dual 4Ω V.C.	• 500w/1000w

REBEL SERIES SUBWOOFERS



- Poly Glass Fiber Capped Cone
- Wave Roll Surround
- Twin Poly Cotton Dual Roll Spiders
- Woven Round Tinsel Leads
- Powder Coated Stamped Steel Basket
- 65oz High Ferrite Magnet
- Dual 2" 4 Ohm CCAW Voice Coils
- 5-Way Binding Post Terminals

REBEL10	10" Dual 4Ω Voice Coil	• 500w/1000w
REBEL12	12" Dual 4Ω Voice Coil	• 500w/1000w
REBEL15	15" Dual 4Ω Voice Coil	• 500w/1000w

V SERIES SUBWOOFERS



- Poly Mica Cone & Woven Glass Fiber Dust Cap
- 1" N-Roll Polyester Surround
- Woven Round Tinsel Leads
- Stamped Steel Basket
- 40oz Flux Ferrite Y40 Magnet
- 15mm Peak to Peak X-Max
- Dual 1.5" 4 Ohm Voice Coils

V10	10" Dual 4Ω Voice Coil	• 250w/500w
V102	10" Dual 2Ω Voice Coil	• 250w/500w
V12	12" Dual 4Ω Voice Coil	• 250w/500w
V122	12" Dual 2Ω Voice Coil	• 250w/500w

V SERIES SPEAKERS



- Heavy Gauge Steel Basket
- 20mm Silk Dome Tweeters (excl. VX69)
- Multi Mounting Hardware
- UV Protected Poly Injected Cone
- Butyl Rubber Surround
- Pure Copper Voice Coils
- VX69 features 2" Midrange & 13mm Mylar Tweeter

VK6	6-1/2" Component Set	• 250w Peak
VX5	5-1/4" Coaxials	• 200w Peak
VX6	6-1/2" Coaxials	• 250w Peak
VX68	6 x 8" Coaxials	• 250w Peak
VX69	6 x 9" Coaxials	• 300w Peak

CK STAGE III SPEAKERS



- Shallow Cast Basket
- 28mm Silk Dome Tweeter
- Tweeter Mounting Bridge
- Woven Carbon Cone
- Butyl Rubber Surround
- 35mm Kapton Voice Coils
- Audiophile Grade Crossovers

CK6iii	6-1/2" Convertible Set	• 250w Peak
CT1	25mm Silk Dome Tweeters	
CT1A	25mm Aluminum Dome Tweeters	
CT1	28mm Silk Dome Tweeters	