



WIRELESS MICS

PDWM2500

Dual VHF Wireless Mic System – Includes 2 Handheld Microphones; Power & Low Battery Indicators; Dual RF Indicators; Dual AF Level Meters; Dual Volume Controls; 1/4" Mixed Output; Operation Range up to 240'.



PDWM4400

4 Mic VHF Lavalier/Headrest System – Includes 4 Belt Pack Transmitters w/Lavalier and Headset Mics; Power & Low Battery Indicators; RF Indicators; AF Level Meters; Individual Volume Controls; 1/4" Mixed Output; Operation Range up to 240'.



PDWM94

Dual Function Wireless/Wired Mic System – Complete Wireless System; 3 Position Mic Switch; Operating Range Up To 45'; XLR to 1/4" Cable Included.



MICROPHONE PA AMPLIFIER

PA105

80w Microphone PA Amplifier – 20w Mono @ 8 Ohms, Power On/Off LED, LED Level Display, Master Volume Control, Tone Control, Mic 1 & 2 Volume Controls, 110/220v, Unswitched AC Outlet, Phono & RCA Aux Inputs.

PA205

120w Microphone PA Amplifier – 40w Mono @ 8 Ohms, Power On/Off LED, LED Level Display, Master Volume Control, High/Mid/Low Tone Controls, Mic 1 & 2 Volume Controls, 110/220v, Unswitched AC Outlet, Phono & RCA Aux Inputs.

MIXERS

PM4001

19" Rack Mount Mixer – 2 Phono/6 Line/1 Aux Mic Inputs, XLR Mic Input w/Bass & Treble Control, Auto Mute Talkover, BNC 12v Light Jack, Removable Assignable Crossfader, 14 Band Stereo EQ, Cue Assign & Level Controls, Master & Recording Output



2-Way Stage Monitors

Features: Heavy Duty Ported MDF Construction w/Reinforced Corners & Built-In Handles, 10"x18" Super Horn Mid/Tweeter, 1" Titanium Compression Driver, Non-Pressed Paper Cone w/Cloth Edge, Dual Speakon & Dual 1/4" Jacks, 8 Ohms

PASC12

12" 2-Way Stage Monitor – 12" Woofer w/75oz Magnet, FR: 40Hz-20kHz, 300w RMS / 600w Peak, Crossover Frequency: 3kHz, 25.6" w x 17.3" h x 13" d.



15" Professional Premium PA Woofer

PPA15

15" Professional Premium PA Woofer 800 Watts Max / 250 Watts RMS, 70oz Magnet, 2.5" Voice Coil, 8 Ohm Impedance, Cloth Edge Suspension



12" 2-Way Speaker Cabinet

PPHP1259

2-Way Speaker Cabinet – 500 Watts Max / 250 Watts RMS, FR:47Hz-18kHz, SPL:92dB, 8 Ohm Impedance



Amplified 2-Way Loudspeakers

Features: Compression Driver with 1-3/4" Titanium Diaphragm, Full Featured 3ch Mixer, Dual XLR and 1/4" Mic Inputs, XLR & Stereo RCA Line Input, XLR & 1/4" Line Outputs, Master Volume/Bass/Treble Controls, 35mm Speaker Stand Mount.

PPHP1292A

Powered 12" 2-Way Loudspeaker – 12" Woofer, FR: 40Hz-22kHz, 200w RMS / 800w Peak, Crossover Frequency: 2.5kHz, 19" w x 14-1/2" d x 24-1/2" h.

PPHP1592A

Powered 15" 2-Way Loudspeaker – 15" Woofer, FR: 30Hz-22kHz, 300w RMS / 1000w Peak, Crossover Frequency: 2.2kHz, 20" w x 16" d x 28-1/2" h.



2-WAY SPEAKER CABINETS

PMBH1039

2-Way Speaker Cabinets – 125w RMS/250w Peak, Heavy Duty Construction, 1-4x10" Midrange/Tweeter, 10" Woofer, Dual Ports, FR: 55Hz-19kHz.

PMBH1239

2-Way Speaker Cabinets – 150w RMS/300w Peak, Heavy Duty Construction, 1-4x10" Midrange/Tweeter, 12" Woofer, Dual Ports, FR: 50Hz-19kHz.

PMBH1539

2-Way Speaker Cabinets – 200w RMS/400w Peak, Heavy Duty Construction, 1-4x10" Midrange/Tweeter, 1-15" Woofer, Dual Ports, FR: 45Hz-19kHz.

4-WAY TWEETER CABINET

PMBHTW4

4-Way Tweeter System – 4 Motorola 3" Super Tweeters, 100w RMS / 200w Peak, FR: 3.5kHz-20kHz.



TW12/TW125

HORN TWEETERS

TW105

3-3/4" Super Horn Tweeter – 75w RMS / 150w Peak.

TW12

Wide Dispersion Piezo Horn – 5-3/4" x 2-5/8" piezo tweeter, 75w RMS / 150w Peak

TW125

Wide Dispersion Piezo Horn – 7-1/2" x 3-1/4" piezo tweeter, 75w RMS / 150w Peak.