



### 5000.1D EVO 1

1 x 5000 W RMS @ 1Ω 12.6V      1 x 6530 W RMS @ 1Ω 14.4V  
 1 x 2750 W RMS @ 2Ω 12.6V      1 x 3592 W RMS @ 2Ω 14.4V  
 1 x 1513 W RMS @ 4Ω 12.6V      1 x 1975 W RMS @ 4Ω 14.4V

### 3000.1D EVO 1

1 x 3000 W RMS @ 1Ω 12.6V      1 x 3918 W RMS @ 1Ω 14.4V  
 1 x 1650 W RMS @ 2Ω 12.6V      1 x 2155 W RMS @ 2Ω 14.4V  
 1 x 908 W RMS @ 4Ω 12.6V      1 x 1185 W RMS @ 4Ω 14.4V

### 2000.1D EVO 1

1 x 2000 W RMS @ 1Ω 12.6V      1 x 2612 W RMS @ 1Ω 14.4V  
 1 x 1100 W RMS @ 2Ω 12.6V      1 x 1437 W RMS @ 2Ω 14.4V  
 1 x 605 W RMS @ 4Ω 12.6V      1 x 790 W RMS @ 4Ω 14.4V

### 1600.1D EVO 1

1 x 1600 W RMS @ 1Ω 12.6V      1 x 2090 W RMS @ 1Ω 14.4V  
 1 x 880 W RMS @ 2Ω 12.6V      1 x 1149 W RMS @ 2Ω 14.4V  
 1 x 484 W RMS @ 4Ω 12.6V      1 x 632 W RMS @ 4Ω 14.4V

### 1200.1D EVO 1

1 x 1200 W RMS @ 1Ω 12.6V      1 x 1567 W RMS @ 1Ω 14.4V  
 1 x 660 W RMS @ 2Ω 12.6V      1 x 862 W RMS @ 2Ω 14.4V  
 1 x 363 W RMS @ 4Ω 12.6V      1 x 474 W RMS @ 4Ω 14.4V

### 400.2D EVO 4

2 x 200 W RMS @ 2Ω 12.6V      2 x 261 W RMS @ 2Ω 14.4V  
 2 x 110 W RMS @ 4Ω 12.6V      2 x 144 W RMS @ 4Ω 14.4V  
 1 x 400 W RMS @ 4Ω 12.6V      1 x 522 W RMS @ 4Ω 14.4V

### 1200.4D EVO 4

4 x 300 W RMS @ 2Ω 12.6V      4 x 392 W RMS @ 2Ω 14.4V  
 4 x 165 W RMS @ 4Ω 12.6V      4 x 215 W RMS @ 4Ω 14.4V  
 2 x 600 W RMS @ 4Ω 12.6V      2 x 784 W RMS @ 4Ω 14.4V

### 800.4D EVO 4

4 x 200 W RMS @ 2Ω 12.6V      4 x 261 W RMS @ 2Ω 14.4V  
 4 x 110 W RMS @ 4Ω 12.6V      4 x 144 W RMS @ 4Ω 14.4V  
 2 x 400 W RMS @ 4Ω 12.6V      2 x 522 W RMS @ 4Ω 14.4V

### 800.4D EVO 2

4 x 200 W RMS @ 1Ω 12.6V      4 x 261 W RMS @ 1Ω 14.4V  
 4 x 110 W RMS @ 2Ω 12.6V      4 x 144 W RMS @ 2Ω 14.4V  
 2 x 400 W RMS @ 2Ω 12.6V      2 x 522 W RMS @ 2Ω 14.4V

### 400.4D EVO 4

4 x 100 W RMS @ 2Ω 12.6V      4 x 131 W RMS @ 2Ω 14.4V  
 4 x 55 W RMS @ 4Ω 12.6V      4 x 72 W RMS @ 4Ω 14.4V  
 2 x 200 W RMS @ 4Ω 12.6V      2 x 261 W RMS @ 4Ω 14.4V



### SOUNDIGITAL AMPS FEATURE:

- Linear Twin Power Supplies
- Efficiency Over 90%
- Intelligent Protection Circuitry
- On-Board Crossovers
- Bass Boost

### 250.1D NANO 2

1 x 250 W RMS @ 1Ω 12.6V      1 x 300 W RMS @ 1Ω 14.4V  
 1 x 250 W RMS @ 2Ω 12.6V      1 x 300 W RMS @ 2Ω 14.4V

### 250.2D NANO 4

2 x 135 W RMS @ 2Ω 12.6V      2 x 300 W RMS @ 2Ω 14.4V  
 2 x 85 W RMS @ 4Ω 12.6V      2 x 170 W RMS @ 4Ω 14.4V  
 1 x 250 W RMS @ 4Ω 12.6V      1 x 300 W RMS @ 4Ω 14.4V