

ONLY AVAILABLE TO AUTHORIZED DEALERS IN KS, MO, IA, NE AND SOUTHERN ILLINOIS

People ask all the time "Are the new Reference amps as good as the old ones?" Think about it! While they were astonishing at the time, times change... Parts get better and engineers get smarter. The new Reference amps are nothing short of phenomenal!

REFERENCE AMPLIFIERS



- Non-Regulated Power Supplies on Class A/B Full Range Models
- Fully Regulated Power Supplies on Class G Monoblock Models
- PCB Features: Separated Capacitor Charging & Discharging; Separated High & Low Current Sections; High Current Bipolar Transistors & MOSFETS
- Balanced Outputs In Preamp Section
- Triple Darlington Transistor Driver & Output Stages
- 2oz PCB Copper & Large Solid Copper Ground Planes
- Numerous Guard Traces Between The Signal Traces
- Top Of The Line Potentiometers
- Extended High & Low Crossover Range

REF1.1000	1 x 1000 RMS @ 2Ω	1 x 1000 RMS @ 1Ω
REF1.500	1 x 500 RMS @ 2Ω	1 x 500 RMS @ 1Ω
REF2.640	2 x 190 RMS @ 4Ω	2 x 320 RMS @ 2Ω
REF2.370	2 x 110 RMS @ 4Ω	2 x 185 RMS @ 2Ω
REF4.760	4 x 115 RMS @ 4Ω	4 x 160 RMS @ 2Ω
REF4.400	4 x 70 RMS @ 4Ω	4 x 100 RMS @ 2Ω
REF5.1000	4 x 95 + 1 x 270 RMS @ 4Ω	4 x 135 + 1 x 460 RMS @ 2Ω

RUBICON AMPLIFIERS



- Midnight Blue Finish w/Brushed Accents
- Double Sided SMD Circuit Boards
- Detent Crossovers & Gain Adjustment
- 12dB Variable Crossovers
- 6db & 12dB Variable Bass Boost
- Low or High Level Inputs
- 180° Phase Control (Mono Models)
- Class D Strappable w/2Ω
- 4ga Power & 8ga Speaker Terminals
- Includes Dash Mount Remote Gain Control (excl RUB2.250, RUB4.600, RUB5.800)

Boasting a gorgeous yet aggressive blue hairline finish, there's no mistaking the fact that the Rubicon amplifiers stand for what Soundstream intended many years ago... Strong quality and strong identity - These boys are at the top of their game with the most modern technology available.

RUB1.2500D	1 x 1700 RMS @ 2Ω	1 x 2500 RMS @ 1Ω
RUB1.1600D	1 x 1100 RMS @ 2Ω	1 x 1600 RMS @ 1Ω
RUB1.1000D	1 x 800 RMS @ 2Ω	1 x 1000 RMS @ 1Ω
RUB1.400	1 x 250 RMS @ 4Ω	1 x 400 RMS @ 2Ω
RUB2.600	2 x 180 RMS @ 4Ω	2 x 300 RMS @ 2Ω
RUB2.250	2 x 75 RMS @ 4Ω	2 x 125 RMS @ 2Ω
RUB4.600	4 x 100 RMS @ 4Ω	4 x 150 RMS @ 2Ω
RUB5.800	4 x 70 + 1 x 200 RMS @ 4Ω	4 x 115 + 1 x 340 RMS @ 2Ω

STEALTH AMPLIFIERS



- Stackable Chassis
- Anodized Black Chassis w/Chrome Accents
- Double Sided SMD Circuit Boards
- Detent Crossovers & Gain Adjustment
- 12dB Variable Crossovers
- 12dB Variable Switched Bass Boost
- Low or High Level Inputs
- 4ga Power & 8ga Speaker Terminals
- Includes Dash Mount Remote Gain Control (STL1.1200D)

Stealth Amplifiers offer not only a small footprint, they're also stackable. While most compact amps in today's marketplace are Class D, Stealth Amplifiers are all Class A/B for the purest uncolored sound reproduction.

STL1.1200D	1 x 700 RMS @ 2Ω	1 x 1200 RMS @ 1Ω
STL2.560	2 x 150 RMS @ 4Ω	2 x 280 RMS @ 2Ω
STL4.500	4 x 80 RMS @ 4Ω	4 x 125 RMS @ 2Ω
STL6.620	4 x 60 + 2 x 100 RMS @ 4Ω	4 x 80 + 2 x 150 RMS @ 2Ω

UNDER SEAT SUBWOOFERS



- 150w Amplifier Built-in
- 200mV-3V Input Sensitivity
- Variable 12dB LP Crossover
- Variable 12dB 45Hz Bass Boost
- 180° Phase Switch
- Remote Gain Control Included
- Dimensions: 3"h x 9.5"w x 14.5L

USB8A	8" Under Seat Amplified Enclosure w/Remote Gain
--------------	-------------------------------------------------

STEALTH SUBWOOFER ENCLOSURE



Dimensions Only 30" Wide x 14.5" Tall x 5.25" Deep!

STEALTH13BX	.6 cu ft Preloaded Enclosure w/Embroidered Accents
--------------------	----------------------------------------------------

**ONLY AVAILABLE TO AUTHORIZED DEALERS IN
 KS, MO, IA, NE AND SOUTHERN ILLINOIS**
SPLX SUBWOOFERS


- Cast Aluminum Frame
- Dual 2 Ohm 3" CCAW Coils
- Epoxy Coated Spruce Pulp Cone
- Dual NOMEX Spiders

Competitors who use music like the powerful rumble of low bass. Last year we introduced the new SPLX-HX series that had increased power handling, lower F's, and longer Xmax.

SPLX122HX 12" Dual 2Ω Voice Coil • 1000w RMS

SPLX152HX 15" Dual 2Ω Voice Coil • 1000w RMS

TARANTULA SUBWOOFERS


- Transparent Smoke Cone Can Be Backlit For Custom Installations
- High Roll Rubber Surround
- Proprietary 7pc Cast Aluminum Basket
- Twin Progressive Spider Suspension
- Dual 4 Ohm 2.5" Voice Coil

The new T6 subwoofers are the next generation in the Tarantula Series. As times change, so do people and music. Today calls for gut wrenching low bass. Both the 12" and 15" T6 have resonant frequencies 5Hz lower than the T5. Plus, excursion has been increased by 43% on both sizes!

T612 12" Dual 4Ω Voice Coil • 900w RMS

T615 15" Dual 4Ω Voice Coil • 1000w RMS

STEALTH SUBWOOFERS


- Proprietary Cast Aluminum Basket
- Inverted Motor Assembly
- Solid Aluminum Cone
- 2" Mounting Depth
- 5" Voice Coil
- Semi Circular Frame Venting

Simply put, this woofer is the shallowest woofer on the market. It is a full 13.25" subwoofer that can play not only in a tiny .5 cubic foot enclosure, but without losing low bass extension. Perfect for applications in doors, under seats, footwells, and in trucks.

STEALTH13 13.25" Single 4Ω Voice Coil • 200w RMS

PICASSO SUBWOOFERS


- Polypropylene Injection Molded Cone
- NBR Rubber Surround
- Conex/Cotton Composite Spider
- Texture Coating On Steel Basket
- Suspension Integrated Tinsel Leads
- Vented Back Plate

These aggressive new subs are engineered from the ground up. The new motors yield more power handling than the previous drivers and are specific per size. Past experience proves that one size fits all motors for 10"-15" subs do not yeild top performance.

PXW10 10" Dual 4Ω Voice Coil • 350w RMS

PXW102 10" Dual 2Ω Voice Coil • 350w RMS

PXW12 12" Dual 4Ω Voice Coil • 400w RMS

PXW122 12" Dual 2Ω Voice Coil • 400w RMS

PXW15 15" Dual 4Ω Voice Coil • 500w RMS

PXW152 15" Dual 2Ω Voice Coil • 500w RMS



- Shallow Mount Version
- Only 2.375" Mounting Depth
- Optimum Sealed: 0.60 cu ft

PXW10T 10" Dual 2Ω Voice Coil • 160w RMS • Shallow Mount

ARACHNID SUBWOOFERS


- Polypropylene Injection Molded Cone
- Butyl Rubber Stitched Surround
- Poly Cotton Spider
- Texture Coating On Steel Basket
- Vented Back Plate
- 8ga Compression Wire Terminals

You spoke, and we listened. You demanded an affordable subwoofer with the Soundstream reputation, and we delivered. Versatility of the Arachnid's engineering allows for its use in typical sealed and ported enclosures, giving you the best bang for your buck.

STW12S 12" Dual 4Ω Voice Coil • 400w RMS

**ONLY AVAILABLE TO AUTHORIZED DEALERS IN
KS, MO, IA, NE AND SOUTHERN ILLINOIS**

A big 3" voice coil in the woofer of RF60C yields greater woofer control, while the treated paper cone gives a smooth balanced sound. Keeping up with the lows is a 1" silk dome tweeter.

REFERENCE COMPONENTS



- Cast Aluminum Woofer Basket
- Treated & Pressed Paper Woofer Cone
- Butyl Rubber Surround
- 3" High-Temperature Voice Coil
- 1" Silk Tweeter With Ferrofluid Cooling
- 18dB/Octave Passive Crossover
- Selectable Low Pass Filter: 2.5/2.8kHz
- 4 Tweeter Attenuation Points
- Overload Bulb & Tweeter Protection

RF60C 6.5" Reference Component Set • 180w

RUBICON COMPONENTS



- Diamond Cut Cast Aluminum Basket
- Polypropylene Cone
- Butyl Rubber Surround
- 1.25" 4 Ohm Voice Coil
- Vented Voice Coil Former
- 1" Silk Tweeter With Ferrofluid Cooling
- Neodymium Magnet
- Swivel, Flush, or Surface Mounting
- 12dB Crossover w/ Tweeter Protection
- -3, -6dB Tweeter Attenuation

1.25" Voice Coil with Polypropylene cone & 1" silk dome tweeter make the Rubicon series components a great upgrade from boring factory speakers. Ferro fluid and former venting keep everything cool.

RBC6 6.5" Rubicon Component Set • 150w

ARACHNID COMPONENTS



- Zolon Coated Low Resonance Basket
- 20oz. Magnet
- Rubber Magnet Cover
- White Zirconium Coated Cone
- Rubber Surround
- 1" Aluminum Voice Coil
- 13mm Super Dome Tweeter

SC6T 6.5" Arachnid Component Set • 80w

TARANTULA FULL RANGE



- Bi-Ampable Operation
- 1" Kapton Coil Former
- Zolon Coated Stamped Steel Basket
- Black Zirconium Cone
- 1" Swivel Silk Dome Tweeter
- Butyl Rubber Surround
- 3 Ohm Impedance
- Passive Crossovers Included
- CONEX Spider

Black Zirconium coated cones, Ferrofluid cooling, 1-inch silk dome tweeters and progressively slanted surrounds all combine to make the Tarantula line of coaxial speakers the best bet for those who insist on the sound quality of a component system.

SST8.2 8" 2-Way • 170w

SST6.5 6.5" 2-Way • 120w

SST5.7 5 x 7" 2-Way • 150w

SST6.9 6 x 9" 2-Way • 150w

PICASSO FULL RANGE



- 1" Aluminum Coil Former
- Stamped Steel Basket
- Carbon Injection Cone
- Mylar Midrange & Tweeters
- Butyl Rubber Surround
- 3 Ohm Impedance

PCT693 6 x 9" 2-Way • 130w

PCT573 5 x 7" 2-Way • 110w

PCT462 4 x 6" 2-Way • 75w

PCT653 6.5" 3-Way • 90w

PCT502 5.25" 2-Way • 80w

PCT402 4" 2-Way • 65w

ARACHNID FULL RANGE



- Zolon Coated Low Resonance Basket
- White Zirconium Coated Cone
- Rubber Surround
- 1" Aluminum Voice Coil
- Piezo Super Dome Tweeter
- White Terminal Connections
- Rubber Magnet Cover
- Impedance: 4 Ohm

SF693T 6 x 9" 3-Way • 100w

SF652T 6.5" 2-Way • 60w

**ONLY AVAILABLE TO AUTHORIZED DEALERS IN
KS, MO, IA, NE AND SOUTHERN ILLINOIS**

TWEETERS

- TWS.1** 1" Soft Dome Tweeter w/3 Mounting Options • 110w
- TWS.4** 1" Tantalum Dome Tweeter w/2 Mounting Options • 110w



SUBWOOFER GRILLS

Chrome Plated Cast Aluminum Tarantula Woofer Grills



- GRILL10X** 10" Chrome Plated Cast Aluminum Tarantula Woofer Grill
- GRILL12X** 12" Chrome Plated Cast Aluminum Tarantula Woofer Grill
- GRILL15X** 15" Chrome Plated Cast Aluminum Tarantula Woofer Grill

SIGNAL PROCESSORS



MPQ4US

- 4 Band Parametric EQ w/USB Input**
- On Board USB/SD/MMC Input
- 2 Selectable Balanced RCA Inputs
- Front, Rear, Sub RCA Outputs
- 4 Band 18dB Equalizer
- Independent Subwoofer Level Control
- Blue Backlit Control Knobs



BX10

- Digital Bass Processor**
- Dash Mount Remote Control
- Parametric Bass Control
- PFM Subsonic Filter
- PWM High Headroom Power Supply
- Output Level: 13.5 Volt



BX12

- Digital Bass Processor**
- Dash Mount Remote Control
- Parametric Bass Control
- PFM Subsonic Filter
- PWM High Headroom Power Supply
- Output Level: 13.5 Volt



INT2BX

- OEM Integration w/ Bass Processor**
- 5 Channel High Level Inputs
- Independent 4-30V Input Sensitivity
- Variable 30-80Hz Bass EQ
- Variable 0-12dB Bass Boost
- Variable Boost Q
- 15-50Hz Subsonic Filter
- Remote Subwoofer Gain Control
- Front, Rear, Sub RCA Output
- Signal Sense Auto Turn On

