

T.200 SERIES



- Black Anodized 60oz Motor Structure
- Durable Powder Coated Steel Basket
- Heavy Gauge Braided Tinsel Leads
- UV Treated Foam Surround
- Non-Pressed Paper Cone
- Silk Screened Poly Dust Cap
- 4 Layer 1.5" Copper Voice Coil

	Size	Ohms	RMS/Peak	Motor Size	Weight	Xmax	Response	Sensitivity
T2008S	8"	4Ω	200w/400w	60oz	6.5lbs	14mm+/-	30-300Hz	85dB
T20010S	10"	4Ω	200w/400w	60oz	7lbs	14mm+/-	28-250Hz	85.2dB
T20012S	12"	4Ω	200w/400w	60oz	8lbs	14mm+/-	28-250Hz	86.5dB

T.400 SERIES



- Black Anodized 105oz Motor Structure
- Durable Powder Coated Steel Basket
- Heavy Gauge Braided Tinsel Leads
- UV Treated Foam Surround
- Non-Pressed Paper Cone
- Silk Screened Poly Dust Cap
- 4 Layer 2" Copper Voice Coil
- Nickel Plated Push Terminals
- Rubber Mounting Gasket

	Size	Ohms	RMS/Peak	Motor Size	Weight	Xmax	Response	Sensitivity
T40010S	10"	4Ω	400w/800w	105oz	10lbs	18mm+/-	25-250Hz	88.9dB
T40010D	10"	Dual 4Ω	400w/800w	105oz	10lbs	18mm+/-	25-250Hz	88.7dB
T40012S	12"	4Ω	400w/800w	105oz	11lbs	18mm+/-	25-250Hz	89.2dB
T40012D	12"	Dual 4Ω	400w/800w	105oz	11lbs	18mm+/-	25-250Hz	90.1dB

T.600 SERIES



- Black Anodized 200oz Motor Structure
- Durable Powder Coated Steel Basket
- Heavy Gauge Braided Tinsel Leads
- 5 Layer UV Treated Foam Surround
- Synthetic Blend Cone
- Silk Screened Poly Dust Cap
- 4 Layer 2.5" Copper Voice Coil
- Nickel Plated Push Terminals
- Rubber Mounting Gasket

	Size	Ohms	RMS/Peak	Motor Size	Weight	Xmax	Response	Sensitivity
T60010D	10"	Dual 4Ω	600w/1200w	200oz	17lbs	22mm+/-	25-250Hz	88.2dB
T60012D	12"	Dual 4Ω	600w/1200w	200oz	18lbs	22mm+/-	25-250Hz	89.5dB
T60015D	15"	Dual 4Ω	600w/1200w	200oz	21lbs	22mm+/-	25-250Hz	91dB

T.1000 SERIES



- Polished Chrome 240oz Motor Structure
- Die Cast Aluminum Coated Frame
- Heavy Gauge Sewn-In Tinsel Leads
- UV Treated EES Foam Surround
- One Piece Kevlar Front Cap with Aluminum Logo
- 4 Layer 2.5" Copper Voice Coil
- Nickel Plated Push Terminals
- Rubber Mounting Gasket

	Size	Ohms	RMS/Peak	Motor Size	Weight	Xmax	Response	Sensitivity
T100010D	10"	Dual 4Ω	1000w/2000w	240oz	20lbs	25mm+/-	25-250Hz	88dB
T100012D	12"	Dual 4Ω	1000w/2000w	240oz	21lbs	25mm+/-	25-250Hz	89.3dB
T100015D	15"	Dual 4Ω	1000w/2000w	240oz	24lbs	25mm+/-	25-250Hz	91.5dB

T.2000 SERIES



- Polished Chrome 600oz Motor Structure
- Unique Cast Aluminum Basket
- Heavy Gauge Sewn-In Tinsel Leads
- UV Treated EES Foam Surround
- One Piece Carbon Fiber Front Cap with Aluminum Logo
- 4 Layer 3" Copper Voice Coil
- Nickel Plated Push Terminals
- Rubber Mounting Gasket

	Size	Ohms	RMS/Peak	Motor Size	Weight	Xmax	Response	Sensitivity
T200010D	10"	Dual 2Ω	2000w/4000w	600oz	46lbs	37mm+/-	20-230Hz	89dB
T200012D	12"	Dual 2Ω	2000w/4000w	600oz	47lbs	37mm+/-	20-230Hz	90.7dB
T200015D	15"	Dual 2Ω	2000w/4000w	600oz	48lbs	37mm+/-	20-230Hz	93dB
T200018D	18"	Dual 2Ω	2000w/4000w	600oz	50lbs	37mm+/-	20-230Hz	94.4dB

T3 COAXIALS



T4C	4" Coaxials	50w/100w
T5C	5.25" Coaxials	50w/100w
T6C	6.5" Coaxials	60w/120w
T57C	5" x 7" Coaxials	60w/120w
T69C	6" x 9" Coaxials	75w/150w
T5S	5.25" Components	100w/200w
T6S	6.5" Components	100w/200w