

\* Please specify transmit frequency when ordering



## BASE STATION / REPEATER AMPLIFIERS

Features: Heavy Duty Heatsink, Front Panel Circuit Breaker, Thermostatically Controlled DC Cooling Fan.



VHF High Band 136-174 MHz

### PA3-1AE3-RXRF

2.5-5W In / 80-150W Out - 20A Current Drain

### PA3-1DE-RXRF

8-15W In / 80-150W Out - 16A Current Drain

### PA3-1FE-RXRF

15-25W In / 80-150W Out - 14A Current Drain

UHF 400-512 MHz

### PA6-1AE-RXRF

1-4W In / 70-100W Out - 20A Current Drain

### PA61BERXRF

8-15W In / 70-100W Out - 16A Current Drain

### PA6-1FE-RXRF

25-40W In / 60-100W Out - 15A Current Drain

## MOBILE AMPLIFIERS

Standard voltage is 13.8 VDC. UHF connectors are standard on mobile amplifiers through 512 MHz. Type N connectors are standard on 800MHz models.



VHF High Band 136-174 MHz

### PA3-1AC

1-4W In / 20-45W Out -

### PA3-1AE3

1-3W In / 70-140W Out -

### PA3-1DE

8-15W In / 70-140W Out -

### PA3-1FE

20-40W In / 70-140W Out -

UHF 400-512 MHz

### PA6-1AC

1-4W In / 25-50W Out -

### PA6-1BC

8-15W In / 25-50W Out -

### PA6-1AE

1-4W In / 70-100W Out -

### PA6-1FE

25-40W In / 60-100W Out -

UHF High Band 806-866 MHz

### PA8-1DD

5-15W In / 50-80W Out -

### PA8-1FD

20-35W In / 50-80W Out -

## HENRY RADIO

### HENRY RADIO Solid State Power Amps

140-165 MHz

#### C130AB02

2 Watts In 100/150 Out. Specify frequency.

#### C130AB10

5/20 Watts In 100/150 Out. Specify frequency.

#### C130AB30

20/40 Watts In 100/150 Out. Specify frequency.

#### C130AB10/R

5/20 Watts In 100/150 Out, Repeter version. Specify frequency.

### HENRY RADIO Solid State Power Amps

450-460 MHz

#### C100D02-1

1/5 Watts In 80/110 Out. Specify frequency.

#### C100D10-1

5/20 Watts In 80/110 Out. Specify frequency.

#### C100D30-1

20/40 Watts In 80/110 Out. Specify frequency.



### HENRY RADIO Solid State Power Amps

460-470 MHz

#### C100D02-2

1/5 Watts In 80/110 Out. Specify frequency.

#### C100D10-2

5/20 Watts In 80/110 Out. Specify frequency.

#### C100D30-2

20/40 Watts In 80/110 Out. Specify frequency.

### HENRY RADIO Solid State Repeater Amps

Repeater Amps are rated for continuous transmit duty. Rack mounted – includes cooling fans.

140-165 MHz

#### C130AB30R

20/40 Watts In 100/150 Out. Specify frequency.

#### C250AB30R

30 Watts In 250/300 Out. Specify frequency.

450-470 MHz

#### C100D02R

1/5 Watts In 80/110 Out. Specify frequency.

#### C100D10R

5/20 Watts In 80/110 Out. Specify frequency.

#### C100D30R

20/40 Watts In 80/110 Out. Specify frequency.

#### C200D10R

10 Watts In 180/200 Out. Specify frequency.

#### C200D30R

30 Watts In 180/200 Out. Specify frequency.